

Pipeline 3' 4-Bank

Pipeline 4' 4-Bank

“

When you do what I do, you're attached to the success and longevity of the fixtures that you recommend, and BB&S has never let me down.”

Nicholas Hutaik, DPLighting Designer



Pipeline 1'

PIPELINE REMOTE PHOSPHOR LED SYSTEM™

PIPELINE 4-BANKS

First Remote Phosphor Light Banks

BB&S vastly improves on the classic light bank by adding the benefits of Remote Phosphor technology in the Pipeline 3' and 4' 4-Bank ready to go lighting fixtures.

Cool And Powerful

Pipeline 4-Banks house 3' or 4' (914mm or 1219mm) long, 1-inch (25mm) diameter, Remote Phosphor LED Pipes. Three-foot units offer an output of 12,000 lumens at 100%, while the four-foot outputs a whopping 16,000 lumens! Yet, they run cool and power off 48V for smooth dimming.

Get In Control

With a built-in 4-channel control, Pipeline 4-Banks are fully dimmable (100% to zero) without color shift or flicker. The Control offers 8/16-bit DMX 512/RDM and manual dimming plus strobe capability. Optional soft boxes, grids, and flush mount grids are available to enhance light shaping.

Color Match Any Situation

Pipeline 4-Banks come in 3200°K, 5600°K and the Bi-color model that allows users to dial-in any color temperature between 3200°K and 5600°K and individually tweak. As light intensity is increased or dimmed, there's no affect on color temperature.

Features

- Choose from 3' or 4' lengths
- Power Supply: 48V with powerCON TRUE1 locking AC Cable
- Color Temps: 3200°K, 5600°K or Bi-color
- No color shift
- Built in DMX 512/RDM Controller
- Includes reflector housing

PIPELINE LED SYSTEM SPECIFICATIONS

POWER

- AC Power: 100-240V 50/60Hz
- Max Power Draw: 10 Watts per foot

4-BANKS

- 4' = 16000 Lumens on 160 W max draw
- 3' = 12000 Lumens on 120 W max draw

LED

- Premium LED Array - 50,000 hour life
- High Quality 5600°K -TLCI 95+
- High Quality 3200°K -TLCI 95+
- More than 1000 Lumens per foot

CONTROL

- 8/16-bit DMX 512/RDM, Strobe & Manual dimming

INDIVIDUAL PIPE DIMENSIONS

- Length: 1' / 305mm
- Length: 2' / 610mm
- Length: 3' / 914mm
- Length: 4' / 1219mm
- Width: 1" / 25.4mm

THERMAL

Ambient Operating Temperature: -10° – 40°C / 14° – 104°F



4 Banks are available with optional grids, and softboxes.





PIPELINE REMOTE PHOSPHOR LED SYSTEM™

PIPELINE RAW

The Raws are made for customization, with a 3-pin XLR plug to allow the user to control the electronic configuration. BB&S' makes a 4-way DMX 512/RDM Controller for the Raw, or users can come up with their own solution.

- Ultra High TLCI: 3200°K, or 5600°K
- Available in 1', 2', 3' or 4' lengths
- Flicker-free dimming from 100%-0
- Extremely high light output
- Wide 180° light dispersion
- With 3 Pin XLR
- Optional 4-Channel Controller with 8/16-bit DMX 512/RDM, Strobe & Manual dimming w/48V PSU



Pipeline Raw Pipes and 4-Channel Controller



1 foot 4 Bank

Photometrics

4' 4-Bank

Pipeline 4' 4-Bank 5600°K					
Distance Feet	3.3	6.6	9.8	13.1	14.4
Footcandles	640	160	72	40	24
Distance Meters	1	2	3	4	5
LUX	6876	1720	764	428	276

Pipeline 4' 4-Bank 3200°K					
Distance Feet	3.3	6.6	9.8	13.1	14.4
Footcandles	704	176	80	44	28
Distance Meters	1	2	3	4	5
LUX	5472	1892	840	472	304

3' 4-Bank

Pipeline 3' 4-Bank 5600°K					
Distance Feet	3.3	6.6	9.8	13.1	14.4
Footcandles	498	128	52	32	20
Distance Meters	1	2	3	4	5
LUX	5472	1368	608	344	220

Pipeline 3' 4-Bank 3200°K					
Distance Feet	3.3	6.6	9.8	13.1	14.4
Footcandles	412	104	44	24	16
Distance Meters	1	2	3	4	5
LUX	4444	1112	492	276	176

1' 4-Bank

Pipeline 1' 4-Bank 5600°K					
Distance Feet	3.3	6.6	9.8	13.1	14.4
Footcandles	182.8	45.7	20.4	11.5	7.4
Distance Meters	1	2	3	4	5
LUX	1968	492	220	124	80

Pipeline 1' 4-Bank 3200°K					
Distance Feet	3.3	6.6	9.8	13.1	14.4
Footcandles	149.4	37.5	16.7	9.3	5.9
Distance Meters	1	2	3	4	5
LUX	1608	404	180	100	64

PIPELINE RAW AND BANKS SKU NUMBERS

BANKS

- BBS-3555 1' 4-Bank 3200°K
- BBS-3557 1' 4-Bank 5600°K
- BBS-3529 3' 3200°K
- BBS-3521 3' 5600°K
- BBS-3532 3' Bi-Color 3200°K/5600°K
- BBS-3533 4' 3200°K
- BBS-3535 4' 5600°K
- BBS-3536 4' Bi-Color 3200°K/5600°K

RAW

- BBS-3511 1' 3200°K
- BBS-3513 1' 5600°K
- BBS-3514 2' 3200°K
- BBS-3516 2' 5600°K
- BBS-3517 3' 3200°K
- BBS-3519 3' 5600°K
- BBS-3520 4' 3200°K
- BBS-3522 4' 5600°K
- BBS-3594 4-Way Controller
- BBS-3604 8' / 2.5 Meter 3-Pin XLR cable
- BBS-3605 15' / 5 Meter 3-Pin XLR cable
- BBS-3606 25' / 8 Meter 3-Pin XLR cable



SALES U.S.A.
info@bbslighting.com
Tel 1-800-820-6610
bbslighting.com

INTERNATIONAL SALES
sales@brothers-sons.dk
Tel +45 70 27 42 41
brothers-sons.dk

SALES & RENTAL SUPPORT
info@bbsrentalsupport.com
Tel +46 70 333 78 00
bbsrentalsupport.com

Connect with us on social media

