





Watch the K7 TWIST video HERE

# **K7 TWIST TECH. SPEC.**



### **POWER:**

Typical forward current 700 ma Typical forward voltage: 3V Max. Forward Current: 1050 mA Typical Forward Voltage: 3V

#### LED:

50'000 hour life 3W

High CRI 95+ Typ.

## **DIMENSIONS:** (Head only)

D: 41 mm / 1.61" Weight: 60 g / 0.13 lbs

#### Control:

0-10V drivers DALI drivers DMX - Dimmers

#### Thermal:

Ambient Operating Temperature:  $0-40^{\circ} \, \text{C} / \, 0 - 104^{\circ} \, \text{F}$ 

#### K7 Twist benefits:

Easy installation

Very low power consumption

High reliability

Very compact and versatile unit

50'000 hour lamp life

Available as: 2700K

3000K,

4000K

A range of easy change lenses. Choose between:

narrow

medium

wide, and

elliptical

(It is delivered with narrow lenses)









#### The K7 Twist kit includes...:

6 pcs - K7 Twist: 3m cable, selected LED color temperature and selected housing color

6 pcs - Narrow lens

6 pcs - Honeycomb

6 pcs - Optical mount


6 pcs - Retaining ring

6 pcs - 0-ring base mount

6 pcs - Metal base mount (For angles below 45°)

#### **K7 Twist accessories**

**DALI** Drivers 0 – 10V Drivers **Ouick** connectors Lenses:  $24^{\circ}$ ,  $43^{\circ}$  and  $11^{\circ}$  x  $45^{\circ}$  elliptical **DMX Dimmers** 



**VISIT THE K7 TWIST WEBSITE** 



# THANK YOU!

