

Pro-43 Electrical Tape



High quality Soft PVC Film, coated with a strong rubber based adhesive, easy to use

FEATURES

- Very pliable
- Heat resistant
- RoHS & REACH compliant
- Rubber adhesive
- PVC carrier
- UL510, CSA22.2, VDE Approved

STANDARD SIZES

Length: 66ft (20.12m)
 Width: .75in (19.05mm)

COLORS

- Black

Pro-43 Properties	Value	Test Method
Total thickness	0.172±0.188mm	ASTM D1000
Tensile strength	≥26.2 N/mm	ASTM D1000
Elongation at break	≥200%	ASTM D1000
Adhesion strength _____ to steel _____ to backing	≥1.75 N/cm ≥1.75 N/cm	ASTM D1000
Flammability	Flame retardant	IEC 60454
Dielectric Strength	≥40 kV/mm	IEC 60454

Note: The listed values are required only and not intended to serve as product specifications

RECOMMENDED USES

It is specifically designed for used for wrapping electric wires and cables etc. wrapped wires with a half-lap is best. The last layer should be no tension to prevent flagging.

STORAGE AND SHELF LIFE

The shelf life of the product is five years when stored at 20-30°C, max 65% relative humidity and out of direct sunlight and in its original packaging