

# Pro-98 Electrical Tape

High quality Soft PVC Film, coated with a strong rubber based adhesive, easy to use

## FEATURES

- Very pliable
- Heat resistant
- RoHS & REACH compliant
- Rubber adhesive
- PVC carrier
- UL510, CSA22.2, VDE Approved



## STANDARD SIZES

Length: 66ft (20.12m)  
 Width: 1in (25.4mm) | 2in (50.8mm)

## COLORS

- Black

Pro-98 Properties	Value	Test Method
Total thickness	0.203±0.226mm	ASTM D1000
Tensile strength	≥28 N/mm	ASTM D1000
Elongation at break	≥240%	ASTM D1000
Adhesion strength _____ to steel _____ to backing	≥1.75 N/cm ≥1.75 N/cm	ASTM D1000
Flammability	Flame retardant	IEC 60454
Dielectric Strength	≥40 kV/mm	IEC 60454

Note: The listed values are required only and not intended to serve as product specifications

## RECOMMENDED USES

It is specifically designed for used for wrapping electric wires and cables etc. wrapped wires with a half-lap is best. The last layer should be no tension to prevent flagging.

## STORAGE AND SHELF LIFE

The shelf life of the product is five years when stored at 20-30°C, max 65% relative humidity and out of direct sunlight and in its original packaging