

Terminal Block Connectors

Screw Fixing Connector

A terminal block connector is a stylish and aesthetically designed solution, perfectly suitable for connecting a wide range of lighting setups including most 5V, 12V, and 24V SMD LED Tape Lights or COB LED Strip Lights. Its sleek and transparent design enhances the overall aesthetics of the installation. This connector is remarkably easy to use, requiring minimal effort and expertise. It comes equipped with a convenient screwdriver, making the installation process even simpler.

VARIANTS

- Strip to Strip 2 Pin 10mm
- Strip to Wire 2 Pin 10mm

hitlights.com +1 (855) 768-4135 customerservice@hitlights.com

SPECIFICATIONS

Item NO Connection Type Size(L*W*H) Pin Quantity Pin Distance With Wire or NOT Fixing Method CON-10S-TB-SW-12PK Board to Wire 13.3*11.5*6.4mm 2 4.5 mm With Wire Screw Fixing

CON-10S-TB-SS-12PK

Board to Board 14.6*11.5*6.4mm 2 4.5mm NO Cable Screw Fixing

ELECTRICAL

Voltage 5V-24V DC Current 6A

MATERIAL

Housing Color

TEMP. Resistance

Flame Retardant Rating

Material

CON-10S-TB-SW-12PK

Polycarbonate, Copper

Transparent

UL94V-0

105°C|221°F

CON-10S-TB-SS-12PK

Transparent Polycarbonate, Copper 105°C | 221°F UL94V-0

WORKABLE LED STRIP

Type Light Color IP Rating PCB Width PCB Thickness CON-10S-TB-SW-12PK

LED Strip Flexible & Rigid Mono IP20 10mm 0.25 ~0.35 mm

CON-10S-TB-SS-12PK

LED Strip Flexible & Rigid Mono IP20 10mm 0.25 ~0.35 mm

WORKABLE WIRE DATA

Wire Gauge	20 AWG~16AWG
Cross Section	0.52mm² ~ 1.32mm²
Wire Type	Multi Stranded Sheathed Cable /Flat Wire

WORKING ENVIROMENT

Environment TEMP. -10 ~ 45°C | 50 ~ 113 °F Environment Indoor

DIMENSIONAL DIAGRAM

Item NO.: CON-10S-TB-SW-12PK





TOLERANCE(MM)

Size Range	Tolerance
≤3	±0.10
>3 ≤ 10	±0.15