

# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

#### 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Trade name : Glycol Ether TPM

CAS Number: : 25498-49-1

Chemical characterization : Propylene Glycol Ethers

Chemical name : (2-(2-Methoxy methyl ethoxy)Methylethoxy) Propanol Synonyms : Propanol,(2(2-Methoxymethylethoxy)Methylethoxy),

Tripropylene Glycol Methyl Ether

Identified uses : Solvent

Company Address

Lyondell Chemical Company LyondellBasell Tower, Suite 300

1221 McKinney St. P.O. Box 2583

Houston Texas 77252-2583

**Company Telephone** 

Customer Service 800 321-7000

product.safety@lyb.com

Emergency telephone number

CANUTEC 613 996-6666, CHEMTREC USA 800-424-9300, LYONDELL 800-245-4532

E-mail address : product.safety@lyb.com

Responsible/issuing person

#### 2. HAZARDS IDENTIFICATION

#### **GHS** Classification

Specific target organ systemic toxicity - single exposure Category 3

GHS Classification Scale (1= severe hazard; 4= slight hazard)

#### Label elements

Hazard symbols



Signal word : Warning

**Hazard Statements**: H336 May cause drowsiness or dizziness.

Precautionary : Prevention

**Statements** P261 Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.

P271 Use only outdoors or in a well-ventilated area.



# **Glycol Ether TPM**

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

#### Response

P304 + P340 IF INHALED: Remove person to fresh air and

keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

#### Storage

P403 + P233 Store in a well-ventilated place. Keep container

tightly closed.

P405 Store locked up.

## Disposal

P501 Dispose of contents/ container to an approved waste

disposal plant.

#### Other hazards

No additional information available.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

#### **Substances**

## Ingredients

Chemical name	CAS-No. EC-No.	<u>Weight %</u>	Component Type
Tripropylene Glycol Monomethyl Ether	25498-49-1	> 99.0 %	А

Key:

(A) Substance

#### 4. FIRST AID MEASURES

General advice : Take proper precautions to ensure your own health and safety

before attempting rescue and providing first aid.

Consult a physician/doctor if necessary.

Show this material safety data sheet to the doctor in

attendance.

If inhaled : If overcome by exposure, remove victim to fresh air

immediately.

Give oxygen or artificial respiration as needed.

Obtain emergency medical attention.

Prompt action is essential.

yondellbasell Gen. Variant: SDS CA GHS

# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

In case of skin contact : Remove contaminated clothing as needed.

Wash skin thoroughly with mild soap and water. Flush with lukewarm water for 15 minutes.

If sticky, use waterless cleaner first.

Seek medical attention if ill effect or irritation develops.

In case of eye contact : Thoroughly flush the eyes with large amounts of clean low-

pressure water for at least 15 minutes, occasionally lifting the upper and lower eyelids. If irritation persists, seek medical

attention.

If swallowed : This material may be a slight health hazard if ingested in large

quantities.

If large quantity swallowed, give lukewarm water (pint/ 1/2 liter)

if victim completely conscious/alert.

Do not induce vomiting. Risk of damage to lungs exceeds

poisoning risk.

Obtain emergency medical attention.

Notes to physician

Symptoms : Inhalation may cause CNS depression.

Hazards : May be harmful if swallowed and enters airways.

May be harmful if swallowed.

May cause drowsiness or dizziness.

Treatment : Treatment of overexposure should be directed at the control of

symptoms and the clinical condition of the patient.

#### 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : SMALL FIRE: Use dry chemical, CO2, water spray or regular

foam

LARGE FIRE: Use water spray, water fog or foam. DO NOT

use straight streams

Specific hazards during fire

fighting

: Heat from fire can generate flammable vapor.

When mixed with air and exposed to ignition source, vapors

can burn in open or explode if confined.

Vapors may be heavier than air.

May travel long distances along the ground before igniting and

# yondellbasell Gen. Variant: SDS CA GHS

# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

flashing back to vapor source.

Fine sprays/mists may be combustible at temperatures below

normal flash point.

Heat may build enough pressure to rupture closed containers/spreading fire/increasing risk of burns/injuries.

Cool containers with flooding quantities of water until well after

fire is out.

Withdraw immediately in case of rising sound from venting

safety devices or discoloration of tank.

Always stay away from tanks engulfed in fire.

For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire

burn.

Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for fire-fighters

: Wear positive pressure self-contained breathing apparatus

(SCBA).

Structural firefighter's protective clothing will only provide

limited protection.

## 6. ACCIDENTAL RELEASE MEASURES

Personal precautions : Clean-up to be performed only by trained and properly

equipped personnel.

Environmental precautions : An authoritative evaluation of environmental exposure and risk

indicates that no special risk management practices are

needed to control environmental release.

Methods for containment /

Methods for cleaning up

Eliminate all sources of ignition.

All equipment used when handling this product must be

grounded.

Do not touch or walk through spilled material.

Stop leak if you can do it without risk.

Prevent entry into waterways, sewers, basements or confined

areas.

A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible

material and transfer to containers.

Use clean non-sparking tools to collect absorbed material.

# yondellbasell Gen. Variant: SDS CA GHS

# **Glycol Ether TPM**

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

#### 7. Handling and storage

#### Precautions for safe handling

Advice on safe handling : Keep container tightly closed when not in use.

The potential for peroxide formation is enhanced when this

solvent is used in processes such as distillation.

Use only non-sparking tools.

Properly ground containers before beginning transfer.

Handle empty containers with care.

Flammable/combustible residue remains after emptying. The purging of all empty shipping containers, regardless of the

flashpoint, is recommended when received with air

atmospheres.

Isolate, vent, drain, wash and purge systems or equipment

before maintenance or repair.

Use adequate personal protective equipment.

Observe precautions pertaining to confined space entry.

Fire-fighting class : Not combustible.

## Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

: Store only in tightly closed, properly vented containers away from heat, sparks, open flame and strong oxidizing agents. Store in properly lined steel/stainless steel to avoid slight discoloration from mild steel/copper.

Storage under nitrogen atmosphere is recommended to minimize possible formation of highly reactive peroxides.

Aluminum (5000 series alloys - U.S. Aluminum Association Standard) showed no corrosion after 30 days contact with PM

Acetate, DPM, TPM, PTB, or PM at 71°C (160°F).

Some plastics/rubbers are attacked by Glycol Ethers/Ether

Esters.

This product will absorb water if exposed to air.

Specific end use(s)

: See Section 1.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

## **Control parameters**

Ingredients with workplace control parameters

Consult local authorities for acceptable exposure limits.

# yondellbasell Gen. Variant: SDS CA GHS

# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

#### **Exposure controls**

## Engineering measures

Local exhaust in addition to general room ventilation may be required to meet exposure limit(s).

#### Personal protective equipment

Respiratory protection : No special respiratory protection is recommended under

anticipated conditions of normal use with adequate ventilation. If exposure can exceed the Occupational Exposure Limits, use only approved supplied air respirator with full face mask

operator in positive pressure mode.

Hand protection : Wear chemical resistant gloves such as:

Neoprene.

Eye and face protection : Eye protection such as chemical splash goggles and/or face

shield must be worn when possibility exists for eye contact due to splashing or spraying liquid, airborne particles, or

vapor.

Skin and body protection : Depending on the conditions of use, protective gloves, apron,

boots, head and face protection should be worn. Use PPE that is chemical resistant to the product and

prevents skin contact.

Hygiene measures : Selection of appropriate personal protective equipment should

be based on an evaluation of the performance characteristics of the protective equipment relative to the task(s) to be performed, conditions present, duration of use, and the hazards and/or potential hazards that may be encountered

during use.

Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Use good personal hygiene practices.

Wash hands before eating, drinking, smoking, or using toilet

facilities.

Take off contaminated clothing and wash before reuse. Shower after work using plenty of soap and water.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid Color : Colorless.

Odor : Ether-like odor.

Odor Threshold : No value available.

Flash point : 124 °C

Version 1.2

lyondellbasell

SDS No.: BE123

Gen. Variant: SDS\_CA\_GHS

at 1,013 hPa (760 mm Hg)

Print Date 03/28/2019

Method: PMCC

Lower explosion limit : No Data Available.

Revision Date 04/26/2017

Upper explosion limit : No Data Available.

Flammability (solid, gas) : Not applicable

Oxidizing properties : Not considered an oxidizing agent.

Autoignition temperature : 277 °C

at 1,013 hPa

Molecular weight : 206.28 g/mol

Decomposition temperature : not determined

Melting point/freezing point : -77.8 °C

at 1,013 hPa

Boiling point/boiling range : 242.85 °C

at 1,013 hPa

Vapor pressure : 0.017 hPa

at 20 °C

Density : 0.965 g/cm3

at 20 °C

Water solubility : Miscible

Partition coefficient: n-

octanol/water

: log Pow: 0.31

at 20 °C

Viscosity, kinematic : 5.53 mm2/s

at 25 °C (static)

Relative vapor density : ~ 7.1

at 15 - 32 °C (Air = 1.0)

Surface tension : 68.8 mN/m

1,000 mg/l at 20 °C

Evaporation rate : < 1

(butyl acetate = 1)

Explosive properties : Not explosive

Other Information : Hygroscopic., Volatile Characteristics:, Negligible: <0.1%



# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

: Additional properties may be listed in Sections 2 and 5.

#### 10. STABILITY AND REACTIVITY

Reactivity : Will not occur.

Chemical stability : Stable under recommended storage conditions.

Hazardous reactions : Not expected to occur.

Conditions to avoid : Extended contact with air or oxygen.

The potential for peroxide formation is enhanced when this

solvent is used in processes such as distillation.

Heat, sparks, open flame, other ignition sources, and oxidizing

conditions.

Ignition may occur at temperatures below those published in

the literature as autoignition or ignition temperatures.

Materials to avoid : Strong oxidizing agents.

Moisture and humidity.

May react with oxygen to form peroxides.

However, there is no known evidence that it has nearly the peroxide forming potential as, for example, diethyl ether, etc.

Hazardous decomposition

Thermal decomposition

products

: Not expected to decompose under normal conditions.

: Incomplete combustion will form carbon monoxide and other

toxic vapors.

## 11. TOXICOLOGICAL INFORMATION

Product Summary : The below given information is based on the assessment of

the product including impurities.

Acute toxicity

Acute oral toxicity : Based on acute toxicity values, not classified.

May be harmful if swallowed.

: Ingestion of very large amounts may cause CNS depression,

respiratory failure, and death in cases of severe over-

exposure.

: LD50: 3,400 mg/kg

Species: Rat

Acute inhalation toxicity : Based on acute toxicity values, not classified.

Version 1.2

yondellbasell Gen. Variant: SDS\_CA\_GHS

Glycol Ether TPM

Revision Date 04/26/2017

Print Date 03/28/2019 SDS No.: BE123

: LC0: > 30 ppm

Exposure time: 8 HOURS

Species: Rat

Acute dermal toxicity : Based on acute toxicity values, not classified.

: LD50: 15,400 mg/kg Species: Rabbit

**Skin corrosion/irritation**: Based on skin irritation values, not classified.

Serious eye damage/eye

irritation

: Based on eye irritation values, not classified.

May cause slight transient eye irritation.

Respiratory or skin

sensitization

: Respiratory sensitization

Not classified No study available.

: Skin sensitization Not classified

No adverse effect observed.

Chronic toxicity

Carcinogenicity : Not classified

No adverse effect observed.

Germ cell mutagenicity : Not classified

No adverse effect observed.

Reproductive toxicity

Effects on fertility /

: Not classified

Effects on or via lactation

No adverse effect observed.

Effects on Development : Not classified

No adverse effect observed.

Target Organ Systemic Toxicant - Single exposure

: Classified, May cause drowsiness or dizziness.

: Exposure routes: Ingestion

lyondellbasell

Gen. Variant: SDS CA GHS

# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

Target Organ Systemic Toxicant - Repeated

exposure

: Based on repeated exposure toxicity values, not classified.

Aspiration hazard

: Not classified

May be harmful if swallowed and enters airways.

#### 12. ECOLOGICAL INFORMATION

**Ecotoxicology Assessment** 

Acute aquatic toxicity : Based on acute aquatic toxicity values, not classified.

Chronic aquatic toxicity : Not classified, based on readily biodegradability and low acute

toxicity.

Toxicity to fish

Low acute toxicity to fish

Toxicity to daphnia and other aquatic invertebrates

: Low acute toxicity to aquatic invertebrates.

**Toxicity to algae** : Low toxicity to algae.

**Toxicity to bacteria** : Low toxicity to sewage microbes.

Toxicity to fish (Chronic

toxicity)

: no data available

Toxicity to daphnia and other aquatic invertebrates

(Chronic toxicity)

: no data available

Persistence and degradability

Biodegradability : 60 %

Rapidly degradable.

(After 22 days in a ready biodegradability test)

**Bioaccumulative potential** 

Bioaccumulation : Bioconcentration factor (BCF): 3.16

lyondellbasell

Gen. Variant: SDS CA GHS

# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

Method: (QSAR calculated value)

This material is not expected to bioaccumulate.

Mobility in soil

Surface tension : 68.8 mN/m

1,000mg/l at 20 °C

Distribution among environmental compartments

: Stability in water no data available

: Stability in soil no data available

Low absorption to soil particulates predicted

Additional advice Environmental fate and

pathways

: No additional information available.

#### Results of PBT and vPvB assessment

Not applicable.

Other adverse effects

Additional ecological

information

: No additional information available.

## 13. Disposal considerations

#### Waste treatment methods

Product : Do not dump into any sewers, on the ground, or into any body

of water

Any disposal practice must be in compliance with all Federal,

State/Provincial and local laws and regulations Regulations may vary in different locations

#### 14. TRANSPORT INFORMATION

**BLG (MARPOL Annex II)** 

Description of the goods : POLY(2-8)ALKYLENE GLYCOL MONOALKYL(C1-

C6)ETHER (CONTAINS TRIPROPYLENE GLYCOL METHYL

ETHER)



# Glycol Ether TPM

Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

Pollution category : Z Ship type : 3

#### 15. REGULATORY INFORMATION

If identified components of this product are listed under the TSCA 12(b) Export Notification rule, they will be listed below.

## Other international regulations

#### **Global Inventory Status**

The ingredients of this product are compliant with the following chemical inventory requirements or exemptions.

\*Additional Explanatory Status Statements follow the table, as necessary.

Country/Region	Inventory	Status Description
Australia	AICS	Compliant
Canada	DSL	Compliant
China	IECSC	Compliant
Europe	REACH	See REACH Compliance Statement
Japan	ENCS	Compliant
Korea	KECI	Compliant
New Zealand	NZIoC	Compliant
Philippines	PICCS	Compliant
United States of America	TSCA	Compliant
Taiwan	TCSCA	Compliant

#### REACh status

If the product has been purchased from any company of the LyondellBasell group of companies registered in the European Union, we confirm that the chemical substance in this product has been pre-registered or, where required under REACh, registered, and that we have the intention to proceed with any required registration in accordance with the deadlines set forth in REACh. (Regulation (EU) No. 1907/2006)

Contact product.safety@lyb.com for additional global inventory information.

## 16. OTHER INFORMATION

Material safety datasheet sections which have been updated:

Revised Section(s): 2 4 7 11 14 15 Revision Date April 26 2017



# **Glycol Ether TPM**


Version 1.2 Revision Date 04/26/2017 Print Date 03/28/2019 SDS No.: BE123

HMIS Classification : Health Hazard: 2

Flammability: 1 Physical hazards: 0 2 1 0

NFPA Classification : Health Hazard: 1

Fire Hazard: 1 Instability: 0



#### Disclaimer

This document is generated for the purpose of distributing health, safety, and environmental data.

Information is correct to the best of our knowledge at the date of the SDS publication. It is not a specification sheet nor should any displayed data be construed as a specification. Before using a product sold by a company of the LyondellBasell family of companies, users should make their own independent determination that the product is suitable for the intended use and can be used safely and legally.

SELLER MAKES NO WARRANTY; EXPRESS OR IMPLIED (INCLUDING ANY WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR ANY WARRANTY) OTHER THAN AS SEPARATELY AGREED TO BY THE PARTIES IN A CONTRACT.

Users should review the applicable Safety Data Sheet before handling the product.

This product(s) may not be used in the manufacture of any of the following, without prior written approval by Seller for each specific product and application:

- (i) U.S. FDA Class I or II Medical Devices; Health Canada Class I, II or III Medical Devices; European Union Class I or II Medical Devices;
- (ii) film, overwrap and/or product packaging that is considered a part or component of one of the aforementioned medical devices;
- (iii) packaging in direct contact with a pharmaceutical active ingredient and/or dosage form that is intended for inhalation, injection, intravenous, nasal, ophthalmic (eye), digestive, or topical (skin) administration:
- (iv) tobacco related products and applications, electronic cigarettes and similar devices.

The product(s) may not be used in:

- (i) U.S. FDA Class III Medical Devices; Health Canada Class IV Medical Devices; European Class III Medical Devices:
- (ii) applications involving permanent implantation into the body;
- (iii) life-sustaining medical applications.

All references to U.S. FDA, Health Canada, and European Union regulations include another country's equivalent regulatory classification.

In addition to the above, LyondellBasell may further prohibit or restrict the use of its products in certain applications. For further information, please contact a LyondellBasell representative.



# **Glycol Ether TPM**

Version 1.2 Revision Date 04/26/2017

Print Date 03/28/2019

SDS No.: BE123

#### Disclaimer

Alkylate, Duopac, Duoprime, Filmex, MPDIOL, Polymeg, SAA-100, SAA-101, TBAc, Tebol, T-Hydro, and Tufflo are trademarks owned or used by the LyondellBasell family of companies.

## Numerical Data Presentation

The presentation of numerical data, such as that used for physical and chemical properties and toxicological values, is expressed using a comma (,) to separate digits into groups of three and a period (.) as the decimal marker. For example, 1,234.56 mg/kg = 1 234,56 mg/kg.

#### Language Translations

The information presented in this document has been translated from English by a vendor LyondellBasell believes to be reliable. LyondellBasell and its vendor have made a good-faith effort to verify the accuracy of the translation, but assume no liability or other responsibility for any errors that may have occurred. Please refer to our web site (www.lyondellbasell.com) for the original document written in English.

**End of Material Safety Data Sheet**