

ADMIRAL

141UV-01 S3 ESD HRO SRC

Standard EN ISO 20345:2011

Sizes: 36-47



- Antistaticity
- Impact and compression resistance
- Hydrocarbon resistant outsole
- Puncture resistance
- Energy absorption at the heel
- Upper resistance to water penetration and absorption
- Heat resistant outsole

Three-dimensional *Spyder-Net* lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Two-component *Tyre Pu-Gomma Vibram*® sole. The S-Line design facilitates movements while walking and the optimized cleated profile guarantees lightness and durability



The **SBX** TPU stabilizer is designed to hold the ankle and ensure perfect balance control while walking. This provides stability, comfort and protection on irregular surfaces.

Supremoil full grain leather with water resistance and breathability properties

The **Esolight 1.0** polyurethane midsole made of low-density micro-cells increases energy absorption and provides a correct body weight distribution while walking.

PZ88 fiberglass toe cap and anti-puncture **Txzero** textile insert for extreme lightness, protection and flexibility.



Sole TYRE PU-RUBBER VIBRAM®

- Outsole in Rubber Vibram® HRO
- Thin rubber bottom to optimize lightness
- SRC High slip-resistance
- Fuel oil resistance sole
- High abrasion resistance



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing