



AZUL

203BV-04 S3 CI HI HRO SRC

Standard EN ISO 20345:2011

Sizes 38-48

Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

Two-component ICON PU-RUBBER VIBRAM® sole, guarantees maximum grip and stability on difficult uneven grounds. Slip-resistance sole tested to the SATRA laboratories on metal grating and wooden scaffold boards.



ICON PU-RUBBER VIBRAM®

- Outsole in Rubber Vibram® HRO
- Designed for the use with crampons
- High slip resistance
- Wide, profiled, slip-resistant waist area



BOA® Fit System consists of a micro-adjustable dial, a super-strong lightweight lace and low friction lace guides; engineered for easy, accurate and safe adjustment.

Reflective material.

Full grain Idrotech leather with high water resistance properties.

PZX fiberglass toe cap and anti-puncture Txzero textile insert for extreme lightness, protection and flexibility.



T-01

- Anatomic insole for more comfort
- Supporting PU foam = Dissipation and Energy Return
- Fully lined with conductive micro-perforated fabric to reduce foam wearing



	SRC Slip resistance
	A Antistatic
	P Perforation resistance
	Resistant to an impact of 200 Joules and compression of 15Kn
	E Energy absorption at the heel part
	FO Fuel oil resistance sole
	WRU Water penetration resistant upper
	HI Heat insulation of the sole
	CI Cold insulation of the sole
	HRO Heat resistant outsole

Esolight 1.0 polyurethane midsole with reinforced Over cap. The low-density micro-cell polyurethane increase energy absorption ensuring comfort and lightness.