



MISTRAL

619Z-016 S3 SRC

Standard EN ISO 20345:2011

Sizes 36-47



Three-dimensional Spyder-Net lining with moisture absorption and release properties. Its special three-dimensional and non-deformable textile structure ensures lasting comfort, breathability and elasticity.

SOLID dual density PU guaranties excellent comfort and lightness.



SOLID PU DUAL DENSITY

- SRC Slip resistance sole.
- Fuel oil resistance sole (FO)
- Esolight 1.0+2.0 compound
- Excellent abrasion resistance
- Shock absorbing heel



Quick release lacing System.

Full grain Idrotech leather with high water resistance properties.

Inox steel toecap and anti-puncture for high level of protection.



Exclusive super flexible system made of dual density polyurethane Esolight 1.0 + 2.0. The Esolight 1.0 midsole is made of lower density micro-cell polyurethane so to increase energy absorption, while the outsole is made by high-density Esolight 2.0 polyurethane to guarantee durability and slip resistance.



S-01

- Ultralight
- High abrasion resistant fabric Tessuto ad alta resistenza all'abrasione
- Anatomic insole for better comfort

| | |
|--|--|
| | SRC Slip resistance |
| | A Antistatic |
| | P Perforation resistance |
| | Resistant to an impact of 200 Joules and compression of 15Kn |
| | E Energy absorption at the heel part |
| | FO Fuel oil resistance sole |
| | WRU Water penetration resistant upper |