

KENSUN

AC/DC

Home (110V)

Car (12V)

AIR COMPRESSOR

Product Number: KC-H



INSTRUCTION MANUAL

SAVE THIS MANUAL FOR FUTURE REFERENCE

Dear friend,

We proudly present you with our latest inflator for home or vehicle use. After much research and experience we finally have developed a product to be pleased with. This inflator was created with you in mind and we hope you will be completely satisfied with the quality, design, and performance.

If you are happy, please tell your friends. If you had any issue with the product or our service, please tell us.

You can reach us at

customerservice@kensun.com

or toll free at

**1-855-Kensun-care
(1-855-536-7862)**

As an innovative company, we always want to hear your complaints, comments, and ideas. We do our best to bring you a quality product along with unrivaled customer service. You are guaranteed to be fully satisfied after being treated by our professional and friendly support team.

Your product review is crucial to the success of our business. We will be very grateful if you will do us a favor and take the time to write us a product review on Amazon.

To do so, you can go to



<http://amzn.to/2jnzLFq>

or find the order in “your orders” and click “write a product review”. You can then select the number of stars and write a few words about your experience. It means a lot to us and lets other shoppers know about this great product.

Enjoy!

Your friends at Kensun



Full Two-Year Home Use Warranty

Kensun warrants this product for two years against any defects in material or workmanship. The defective product will be replaced or repaired at no charge. This warranty does not apply to accessories. This warranty gives you specific legal rights and you may have other rights which vary from state to state. This product is not intended for commercial use. If this product is resold or sold by a non-authorized Kensun dealer, then the warranty is void. Should you have any questions, please contact us.

The label on your tool may include the following symbols:

≡direct current


~alternating current

Voltage	DC12V - AC110V
Max Current	<10A
Inflation time at AC	6.5mins
Inflation time at DC	6.5mins
Max Pressure	100PSI
AC Cable Length	71±4 inches
DC Cable Length	110±4 inches
Hose Length	19±2 inches
Operation Temperature	-4~140°F
Dimensions	10.2*4.7*7.8inches
Net Weight	3.3 pounds
Continuous Working time	No more than 30min
Accuracy of gauge	±1psi

**Based on a flat standard tire
195/65R15 to 35 PSI**



FUNCTIONAL DESCRIPTION



INTRODUCTION

Your Inflator is designed to be used in and around the home using its 110 volt cord or in most vehicles with a standard 12 volt socket using its 12 volt adaptor cord. As with any battery-operated appliance, when the Inflator is used in 12 volt mode, performance will vary directly with the battery's state of charge. Naturally, the higher the current drawn by the Inflator, the more the battery power will be decreased.

OPERATING INSTRUCTIONS

⚠ WARNING: Risk of Bursting.

Too much air pressure causes a hazardous risk of bursting. Check the manufacturer's maximum pressure rating for objects being inflated.



TO INFLATE TIRES:



Screw connector on air valve stem


1

Plug power cord into power accessory outlet



2

Press AC or DC button. As soon as the pressure reaches the value you want, press AC or DC button again.



3

ACCESSORY USAGE

1. Screw the air hose connector on the desired nozzle accessory (tapered nozzle or needle inflator) tightly that the air won't leak.
2. Firmly insert the attached nozzle accessory into the inflation port of the object to be inflated.



NOTE: The extension and standard tapered nozzles and the needle inflator nozzle are provided with your Inflator.

BUTTONS



The AC and DC buttons are located on the front of the Inflator just above the pressure gauge.



110V AC Mode

- Always fully extend the 110V AC cord before each use.
- To turn the Inflator on, plug in the 110 volt cord and press the "AC" button.
- To turn the Inflator off, depress the "AC" button.



12V DC Mode

- Always fully extend the 12V DC cord before each use.
- To turn the inflator on, plug the 12 volt adaptor into your vehicle's 12 volt accessory socket and press "DC" button.
- To turn the inflator off, depress the "DC" button.



HOSE AND CORD STORAGE

The hose and cords are stored in the storage compartment on the back and right of the Inflator. The compartment is designed for storing the hose and cord safely inside when the inflator is not used.

MAINTENANCE

Use only mild soap and damp cloth to clean the tool. Never let any liquid get inside the tool; never immerse any part of the tool into a liquid.

IMPORTANT: To assure product SAFETY and RELIABILITY, repairs, maintenance and adjustment (other than those listed in this manual) should be performed by authorized service centers, always using identical replacement parts.

TROUBLESHOOTING

Unit will not start.

Possible Cause	Possible Solution
Wrong button used	Make sure you are using a home AC plug and the AC button is pressed and vice versa.
Fuse in 12 volt adaptor blown.	Replace the fuse.
Cord not plugged in.	Plug tool into a working outlet.
Circuit fuse is blown.	Replace circuit fuse. (If the product repeatedly causes the circuit fuse to blow, discontinue use immediately and have it serviced at a service center or authorized servicer.)
Cord is damaged.	Have cord replaced at Service Center or Authorized Servicer.

Read all instructions before operating product. Failure to follow all instructions listed below may result in electric shock, fire and/or serious injury.

GENERAL SAFETY RULES

SAVE THESE INSTRUCTIONS

KEEP CHILDREN AWAY.

Do not let children play with the tool or extension cord. They should be kept away from work area.

STORE IDLE TOOLS.

When not in use, tools should be stored in dry, and high or locked-up place — out of reach of children.

DON'T FORCE TOOL.

It will do the job better and safer at the rate for which it was intended.

USE THE RIGHT TOOL.

Don't force small tool or attachment to do the job of a heavy-duty tool. Don't use tool for purpose not intended.

AVOID UNINTENTIONAL STARTING.

Don't carry tool with finger on switch. Be sure switch is off when plugging in.

EXTENSION CORDS.

Make sure your extension cord is in good condition. When using an extension cord, be sure to use one heavy enough to carry the current your product will draw. An undersized cord will cause a drop in line voltage resulting in loss of power and overheating.

STAY ALERT.

Watch what you are doing. Use common sense. Do not operate tool when you are tired.

DO NOT OPERATE portable electric tools near flammable liquids or in gaseous or explosive atmospheres. Motors in these tools normally spark, and the sparks might ignite fumes.



ADDITIONAL SAFETY WARNINGS

WARNING! RISK TO BREATHING:

The compressed air from your inflator is not safe for breathing. Never inhale air from your inflator or from a breathing device connected to the inflator.

WARNING! RISK OF ELECTRIC SHOCK:

Turn off and unplug inflator when not in use, when cleaning, or when changing nozzles. Do not expose inflator to rain or wet conditions. Water entering the inflator will increase the risk of electric shock.

WARNING! RISK OF FALLING:

Since the vibration produced by the inflator may cause it to “walk”, do not operate on a high shelf or other surface. Operate at ground or bench level.

WARNING! RISK OF UNSAFE OPERATION:

Do not modify or attempt to repair. Never drill into, weld, or make any modifications to the inflator or its attachments.

Do not operate inflator when car engine is running.

Operate only with the accessories included or those rated for 100 p.s.i. or higher. The use of any accessory not recommended for use with this tool could be hazardous.

- Never “horseplay”. High pressure air is dangerous. Don’t direct air-flow at yourself or others.



WARNING! RISK OF FIRE:

- Inflator can become hot during use. Allow inflator to cool 30 minutes before storing away.
- Never carry the inflator by the hose.

WARNING! This product or its power cord contains lead, a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Wash hands after handling.

California Proposition 65

PLEASE NOTE: If the compressor has been working nonstop for more than 20 minutes, please give it a 10 minute break to cool off before using further.

If you need to fill up a tire from 0 PSI, you can use a jack to lift the car which will make it easier to inflate the tire or alternatively take 5-10 minute breaks if the compressor shuts off especially in hot weather.

WARNING! The use of any accessory not recommended for use with this compressor could be hazardous.

ADDITIONAL SAFETY WARNINGS

Service Information

The Kensun Customer Service Center is staffed with friendly and trained personnel to provide customers with efficient and reliable service and support.

Whether you need technical advice, repair, or genuine factory replacement parts contact Kensun at

1-855-536-7862

customerservice@kensun.com

Please have your order number available when calling for support. In most cases, a Kensun representative can resolve the problem over the phone. If you have a suggestion or comment, give us a call. Your feedback is vital to Kensun.

Thank you for choosing Kensun!



www.kensun.com

KENSUN