

PaveCare™ Black Limestone Restorer & Dark Stone Coloured Sealer

Professional impregnating paving restorer and sealer - for dark paving

PaveCare™ Black Limestone Restorer is a coloured impregnating sealer designed to permanently rejuvenate and restore the appearance of all types of faded dark paving including limestone, slate and concrete pavers.

The professional grade water-based sealer contains a dark coloured pigment which impregnates into the surface of the natural stone and rejuvenates the natural colour.

Once fully cured, the newly treated surface will also resist dirt, grime and algae.



Key facts

- Coloured impregnating sealer designed to permanently rejuvenate and restore dark paving
- Suitable for all types of faded paving and copings including limestone, slate or concrete
- Ready to use - restores the appearance of dark coloured paving
- Resists dirt, grime and algae
- Seals and protects

Order information

Item description:
PaveCare™ Black Limestone Restorer

Pack size: **1L or 5L**

Box quantity: **12 x 1L,
or 4 x 5L**

Order codes:
• 1L: **BLR1**
• 5L: **BLR5**

Application instructions & technical information overview

Preparation

Paving should be sound, clean and free from dirt, dust, oil etc, and must be totally dry. We recommend thorough cleaning using the PaveCare™ Paving & Driveway Cleaner (see page 42 for more information).

PaveCare™ Black Limestone Restorer is supplied ready for use and should be applied when the surface temperature is between 5°C and 30°C.

Application

Shake the container well before use. Wearing appropriate PPE, apply a small quantity of product to the paving using a foam sealant applicator or soft cloth. For rough or textured surfaces, application can be made by brush or foam roller. Apply a complete, even coat over the whole surface - ensuring any excess is removed.

One coat is usually sufficient for most applications, however a second coat will create a greater depth of colour. Allow the first coat to dry prior to applying a second.

Cure/drying times are dependent on temperature and humidity, but as a guide, can accept foot traffic after 4 hours following final application, and will be fully cured after 24 hours at 20°C.

Allow treated surfaces to cure for 24 hours then rinse with a 1:10 dilution of PaveCare™ Paving & Driveway Cleaner to remove any excess sealer.

All tools/equipment should be thoroughly cleaned after use. Waste material should not be emptied into drainage systems.



Handy Hint...

Take care to apply in thin even coats and removing any excess. Two thin layers will give better results than a single heavy coat.

Coverage

This product covers approximately 30m² per litre per coat depending on substrate porosity.

For storage and health and safety information - a full datasheet is available on request.

PLEASE NOTE: PaveCare™ Black Limestone Restorer is not designed for porcelain paving.