



PaveCare™ PRO-810™
Invisible Paving Sealer

Professional solvent based impregnating paving sealer - invisible finish

PRO-810™ Invisible Paving Sealer is a high performance, solvent based surface sealer which has an invisible finish and can be applied to all types of natural stone. It deeply impregnates the stone and protects surfaces from water penetration, staining and the effects of natural weathering whilst remaining breathable. Does not change the colour or texture of the surface and can be used on virtually all porous surfaces, particularly high quality natural stone.

Suitable for outdoor and indoor use.



Key facts

- Professional grade water repellent for porous natural stone and concrete
- Breathable
- Invisible finish
- Seals and protects
- Resists dirt, grime and algae
- Long lasting protection and UV stable
- Deeply impregnating
- High coverage rate

Order information

Item description:
PRO-810™ Paving Sealer

Pack size: **1L, 5L or 25L**

Box quantity: **12 x 1L or 4 x 5L**

Order codes:

- 1L: **PRO8101**
- 5L: **PRO8105**
- 25L: **PRO81025**

Application instructions & technical information overview

Preparation

Substrates should be sound, clean and free from dirt, dust, oil, etc, and must be totally dry. We recommend thorough cleaning using the PaveCare™ Paving & Driveway Cleaner (*see page 42 for more information*). PRO-810™ Invisible Paving Sealer is designed as an invisible coating but may darken very light surfaces slightly. As with all sealants, test on a small inconspicuous area before full application.

Application

The sealer is supplied ready for use and should be applied when the surface temperature of the paving is between 5°C and 25°C. Application may be made by brush, roller or spray. Apply a complete, even coat over the whole surface ensuring any excess is removed.

Allow to dry and repeat application with a thin and even second coat to provide increased protection.

Dryness will normally occur within 2 hours with full curing taking up to 24 hours. Protect from rain until cured.

All tools/equipment should be thoroughly cleaned after use using a suitable solvent such as white spirit. Waste material should not be emptied into drainage systems.



Coverage

PRO-810™ covers approximately 7 - 12m² per litre depending on substrate porosity

For storage and health and safety information - a full datasheet is available on request.



Handy Hint...

We recommend new paving is left for a minimum of 8 weeks before sealing

PLEASE NOTE: PRO-810™ Paving Sealer is not designed for porcelain paving.