

1. PRODUCT AND COMPANY IDENTIFICATION

Product Identifier

Product Name BN Aerosol Lubricoat®

Product Code 1047

Safety Data Sheet Supplier Information:

ZYP Coatings, Inc.

Manufacturer 120 Valley Court

Oak Ridge, TN 37830 www.zypcoatings.com

Telephone (General) (865) 482-5717 8:30 AM - 5:00 PM EST.

Emergency Telephone Number (800) 255-3924 – ChemTel

(813) 248-0585 Outside of US - Call Collect

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

SIGNAL WORD SYMBOL(S)

Danger !

PRIMARY ROUTES OF EXPOSURE Inhalation, contact to the eyes and skin.

HAZARD STATEMENTS

| Flammable | Category 1 | H222 | Extremely flammable aerosol. |
|----------------|-------------|------|---------------------------------------------|
| Gas under | | H280 | Contains gas under pressure; may explode if |
| pressure | | | heated. |
| Eye Irritation | Category 2B | H320 | Causes eye irritation. |
| Inhalation | Category 4 | H332 | Harmful if inhaled. |
| STOT:SE | Category 3 | H335 | May cause respiratory irritation. |
| STOT:SE | Category 3 | H336 | May cause drowsiness or dizziness |

PRECAUTIONARY STATEMENT(S)

| P210 | Keep away from heat / sparks / open flames / hot surfaces No smoking |
|---------------|-----------------------------------------------------------------------|
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Pressurized container: Do not pierce or burn, even after use. |
| P261 | Avoid breathing dust / fume / gas / mist / vapors / spray. |
| P264 | Wash hands thoroughly after handling |
| P271 | Use only outdoors or in well-ventilated area. |
| P304 + P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position |
| | comfortable for breathing. |
| P305 + P351 + | IF IN EYES: Rinse cautiously with water for several minutes. Remove |
| P338 | contact lenses, if present and easy to do. Continue rinsing. |
| P312 | Call a POISON CENTER or doctor / physician if you feel unwell. |
| | |



P337 + P313 If eye irritation persists: Get medical advice / attention.

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50° C/

122° F

P501 Dispose of contents / container in accordance with local / regional /

national / international regulations.

Health 2 Fire 4 Reactivity 0



3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazard Components | | | | | | |
|--------------------------|-------------|------------|--------|--|--|--|
| Chemical Name | Identifiers | | Wt.% | | | |
| Boron Nitride | CAS No. | 10043-11-5 | 15-20% | | | |
| Ethanol | CAS No. | 64-17-5 | 15-20% | | | |
| 2-Propanone | CAS No. | 67-64-1 | 30-35% | | | |
| Propane | CAS No. | 74-98-6 | 10-15% | | | |
| Butane | CAS No. | 106-97-8 | 10-15% | | | |
| Proprietary-Trade Secret | CAS No. | | 1-5% | | | |

4. FIRST AID MEASURES

EYES Flush eyes, including under the eyelids, with large amounts of water. If irritation persists,

seek medical attention.

SKIN Wash thoroughly with mild soap and water, rinse thoroughly.

INGESTION In the event of swallowing, drink 1 to 2 glasses of water to dilute. Do not induce vomiting.

Consult physician immediately.

INHALATION Remove to fresh air. Seek medical attention if symptoms persist. Never give anything by

mouth to an unconscious person.

5. FIRE FIGHTING MEASURES

Extinguishing Media Water spray or fog, dry chemical, carbon dioxide.

Flammability Classification Flammable aerosol.

Special Hazards Arising from the Insufficient data for determination.

Chemical

Hazardous Combustion Products Oxides of carbon.



Specific Protective Equipment and Precautions (Firefighters)

As in any fire, wear self-contained breathing apparatus (SCBA), NIOSH (approved or equivalent) and full protective gear. Extremely flammable liquid packaged in an aerosol spray canister using a flammable gas propellant. Vapors are heavier than air and may travel to sources of ignition and flash back. Avoid high temperatures and static charges. Products of combustion will be created which are toxic when liquid or vapor contacts flame or red hot metal.

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment And Emergency Procedures Particular danger of slipping on leaked/spilled product. Wear protective equipment. Spills from aerosol cans are unlikely and generally of small volume. Spill prevention is generally not a problem. In case of spill or rupture, avoid breathing vapors and ventilate area well. Remove all sources of ignition and use non-sparking equipment. Soak material up with inert absorbents. Allow absorbents to dry then incinerate. Do not incinerate aerosol cans.

Environmental Precautions
Methods And Materials For
Containment And Cleaning Up

Do not allow product to reach sewage system or any water course. No special measures are required; refer to environmental and personal precautions, and other sections of this document.

7. HANDLING AND STORAGE

SAFE HANDLING PRECAUTIONS

Boron Nitride is slippery, and is considered a slip hazard if on a

walkway. Practice good housekeeping.

SAFE STORAGE PRECAUTIONS

Contents under pressure. Do not store in sunlight or heat over 49° C (120° F). Do not spray into open flame or hot surface. High temperatures may cause bursting. Do not puncture or incinerate. Keep out of reach of children. For warehouse storage, pallets and cases should be placed to avoid damage or rupture from material handling equipment. Cap after every use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits/Guidelines

Engineering Measures/Controls Personal Protective Equipment

Provide adequate ventilation to control dust below the TLV.

Protective clothing should be selected specifically for the workplace, depending on concentration and quality of the hazardous substances handled. The chemical resistance of the protective equipment should be in the protective equipment should be in the protective equipment.

inquired from the respective supplier.

Respiratory An appropriate NIOSH-approved respirator for organic vapor must be worn

if exposure is likely to exceed the lowest TLV/PEL rated hazardous $\,$

ingredient as shown below. If respirators are used, a program should be established to assure compliance with OSHA standard 29 CFR§ 1910.134. Safety goggles or side shielded safety glasses are recommended for any

Eye/Face



type of industrial handling.

Hands Use impervious gloves.

Skin/Body Normal work clothing (long-sleeved shirt, long pants, and gloves) is

recommended. With aerosols, skin exposure is not normally experienced.

Exposure Guidelines

Boron Nitride: Guideline ACGIH (TLV): None established (treat as nuisance dust)

10 mg/m³ (Total dust)

5 mg/m³ (Respirable fraction)

None established (treat as nuisance dust) Guideline OSHA (PEL):

15 mg/m³ (Total dust)

5 mg/m³ (Respirable fraction)

Ethanol: Guideline ACGIH (TLV): 1000 ppm

> Guideline OSHA (PEL): 1000 ppm

2-Propanone: Guideline ACGIH (TLV): 500 ppm

Guideline OSHA (PEL): 1000 ppm

1000 ppm or 1800 mg/m³ Propane: Guideline ACGIH (TLV):

> 2500 ppm or 4508 mg/m³ Guideline OSHA (PEL):

Butane: Guideline ACGIH (TLV): 1000 ppm

Guideline OSHA (PEL):

Proprietary-Trade

Secret

Molecular Weight

Guideline ACGIH (TLV): 10 mg/m³ (total dust)

1 mg/m³ (respirable fraction)

15 mg/m³ (total dust) Guideline OSHA (PEL):

Flash Point

5 mg/m³ (respirable fraction)

9. PHYSICAL AND CHEMICAL PROPERTIES

n. ap.

Physical State Odor Alcohol/Acetone Liquid aerosol Color White **Vapor Pressure** Not determined **Specific Gravity** Not determined **Vapor Density** Heavier than air рΗ **Solubility in Water** Not soluble n. ap. Viscosity Not determined **Freezing Point** Not determined **Melting Point** Not determined **Boiling Point** Not determined **VOC Content** 525 - 550 g/L (Calculated) **Percent Volatile** 80-90%

<2° C (<36°C) for liquid

portion

Evaporation Rate Rapid Flash Point Method Closed Cup



10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions.

Incompatible Materials Reacts with oxidizing materials and liquids, strong acids, and strong

bases.

Conditions To Avoid Open flames/sparks/intense heat.

Hazardous Decomposition Products n. ap.

11. TOXICOLOGICAL INFORMATION

Route(s) Of Entry/Exposure Note all values are calculated in accordance with OSHA 29 C.F.R. § 1910

for mixtures.

Ingestion LD₅₀ Oral - rat: 3961 mg/kg **Skin Absorption** LD₅₀ Dermal – rat: 3347 mg/kg

Inhalation LC₅₀ Inhalation – rat (per 4 hours): 15.02 mg/L **Eye Contact** Redness, burning, tearing, or swelling will occur.

Skin Contact Prolonged/repeated contact with skin may cause redness, irritation,

burning, drying and/or cracking of the skin.

Effects of Acute Exposure See sections above for effects on eye contact, skin contact, ingestion,

and inhalation.

Effects of Chronic Exposure

NTP

Exposure limits

CAUTION! Exposure to dust may be irritating to eyes, nose and throat.

Ethanol is listed as A3 (Confirmed animal carcinogen with unknown

relevance to humans).

IARC Ethanol is listed as Group 1 (Carcinogenic to humans) for ethanol in

alcoholic beverages. Some doubt has been expressed regarding whether developmental toxicity can be caused by occupational exposure to ethyl alcohol. Inhalation and dermal exposure in the workplace result in low

blood alcohol concentrations.

(https://www.osha.gov/dts/chemicalsampling/data/CH_239700.html)

ACGIH No ingredient(s) of this product present at levels greater than or equal to

0.1% is identified as probable, possible or confirmed human carcinogen

by ACGIH.

OSHA No ingredient(s) of this product present at levels greater than or equal to

0.1% is identified as probable, possible or confirmed human carcinogen

by OSHA.

Reproductive Effects No data available.

Further Information Quantitative data on the toxicity of this product is not available.

No toxic effects are to be expected when the product is handled

appropriately.

12. ECOLOGICAL INFORMATION

EcotoxicityData is lacking and inconclusive for this product.Persistence/DegradabilityData is lacking and inconclusive for this product.Bio Accumulative PotentialData is lacking and inconclusive for this product.



Mobility in SoilData is lacking and inconclusive for this product.Other Adverse EffectsData is lacking and inconclusive for this product.

13. DISPOSAL CONSIDERATIONS

Description of WasteDo not incinerate aerosol cans. Allow solvents on cleaning rags, papers,

etc. to evaporate, and then dispose of in safety containers. Use and store

to prevent accidental rupture of aerosol cans.

Methods of Disposal Empty cans completely and then puncture it with the approved devices

made for this purpose. The aerosol canisters may then be disposed in the usual trash removal. Consult state, local or national regulations to ensure proper disposal. Disposal must be made according to official regulations.

14. TRANSPORT INFORMATION

UN Number IATA/ICAO: ID8000

DOT, IMDG, IATA IMDG: UN1950 – Ltd. Qty Y Sticker

DOT: Ltd. Qty Y Sticker

Proper Shipping Name IATA – Consumer Commodity

DOT, IMDG, IATA IMDG & DOT - Aerosols Hazard Class(es) DOT - Regulated as Haz

DOT, IMDG, IATA ICAO/IATA – Dangerous or hazardous goods restricted for transport by

air. (9) IMDG – 2.1

Packaging Group DOT – Regulated as Haz

DOT, IMDG, IATA ICAO/IATA – Dangerous or hazardous goods restricted for transport by

air.

IMDG n.a.

Environmental Hazards

DOT, IMDG, IATA n. ap. **Special Precautions** IATA – A112

DOT, IMDG, IATA

| 15. OTHER REGULATORY INFORMATION | | | | |
|----------------------------------|-------------|----------|--|--|
| | Component | CAS No | | |
| SARA 302 | Ethanol | 64-17-5 | | |
| | 2-Propanone | 67-64-1 | | |
| | Propane | 74-98-6 | | |
| | Butane | 106-97-8 | | |
| SARA 313 | Ethanol | 64-17-5 | | |
| | 2-Propanone | 67-64-1 | | |
| | Propane | 74-98-6 | | |
| | Butane | 106-97-8 | | |
| SARA 311/312 | Ethanol | 64-17-5 | | |
| | 2-Propanone | 67-64-1 | | |



| | Propane | 74-98-6 |
|------------------------------------|---------------------------------------------------------------------|----------------------------------------|
| | Butane | 106-97-8 |
| CERCLA | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| CERCLA – Hazardous Substance | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| Clean Water Act Section 311 | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| OSHA | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| WHIMIS | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| Massachusetts Right to Know | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| Pennsylvania Right to Know | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| New Jersey Right to Know | Ethanol | 64-17-5 |
| | 2-Propanone | 67-64-1 |
| | Propane | 74-98-6 |
| | Butane | 106-97-8 |
| California Proposition 65 Warnings | nings This product does not contain any material or ingredient that | |
| | California has found to cause cancer which would require a warning | |
| | under the statute. | |
| TSCA Inventory | All substances contained in this produ | uct are listed in the Toxic Substances |
| • | Control Act Chemical Substance Inver | |
| HMIS (USA) | HEALTH 2 | , |
| • | ELANANAA DILITY | |

FLAMMABILITY REACTIVITY

PERSONAL PROTECTION



NFPA (USA)



Health Flammability Reactivity Specific Hazard

Protective Equipment







16. OTHER INFORMATION

SDS Number: 1047 SDS Revision Number: 2.1.0

SDS Preparation or Revision Date: July 31, 2015
SDS Prepared By: T. Greene
Date Printed July 31, 2015
Telephone Number 865-482-5717

Abbreviations

Not Available n. av. Not Applicable n. ap.

DOT US Department of Transportation

IATA International Air Transportation Association
IMDG International Maritime Code for Dangerous Goods

ICAO International Civilian Aviation Organization

GHS Globally Harmonized System of Classification and Labelling of Chemicals

CAS Chemical Abstract Service

HMIS Hazardous Materials Identification System (US)NFPA National Fire Protection Association (US)

LC50 Lethal concentration, 50 percent

Lethal dose, 50 percent
STOT Specific Target Organ Toxicity

RQ Reportable Quantity

TPQ Threshold Planning Quantity

CERCLA Comprehensive Environmental Response, Compensation and Liability Act

SARA Superfund Amendments and Reauthorization Act

TSCA Toxic Substances Control Act

RTK Right to Know

EPCRA Emergency Planning and Community Right to Know Act

TLV Threshold Limit Values
PEL Permissible Exposure Limits

Although reasonable care has been taken in the preparation of the information contained herein, the manufacturer extends no warranties, makes no representation and assumes no responsibility as to the accuracy or suitability of such information for the application to purchaser's intended purposes or for consequences of its use.



ZYP COATINGS, INC. ("ZYP") MAKES NO WARRANTIES, EXPRESS OR IMPLIED, INCLUDING THE WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. This product is not designed for personal non-commercial use. User is responsible for determining whether this product is fit for a particular purpose and suitable for user's application. IN NO EVENT WILL ZYP BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, OR CONSEQUENTIAL DAMAGES OR LOSSES INCLUDING, BUT NOT LIMITED TO LOSS OF PROFITS, IN ANY WAY RELATED TO THE PRODUCTS REGARDLESS OF THE LEGAL THEORY ASSERTED.

****Caution: HMIS rating are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS ratings are not required on SDS's under 29 CFR§ 1910.1200 the preparer may choose to provide them. HMIS rating are to be used only in conjunction with a fully implemented HMIS program by workers who have received appropriate HMIS training. HMIS is a registered trade and service mark of the NPCA. HMIS materials may be purchased exclusively from J.J. Keller (800) 327-6868.