



EZI-LOADA

A light weight ramp with enhanced safety that delivers on quality, performance and is cost effective.

European designed and engineered, the new Digga Ezi Loada ramps are the most advanced design on the Australian market today.


Features:

- 3 ways of attaching the ramps
 - > Pin (supplied)
 - > Tongue (supplied)
 - > Chain (chain not supplied)
- Patented, fully extruded, double T-beam design, interlocks the rungs into the body of the rail. No physical load is taken by the weld alone. The welds (top & bottom), hold the rung in its fitted position, adding superior strength & durability.
- Certified to the highest international standards CE, GS and TUV guaranteeing the quality and safety of the ramps.
- Reinforced, easy load, lead on/off design are safer and more durable than conventional ramp designs.
- The reinforced bottom rung sits low to the ground ensuring machines don't have to 'step up' onto the ramp. As a result the bottom few rungs won't bend, as so often is the case with current ramp designs. The ride is also much smoother.

CHOOSING THE CORRECT RAMP

A MACHINE'S WHEELBASE LENGTH IS IMPORTANT WHEN CHOOSING RAMPS. A LONGER WHEELBASE WILL DISTRIBUTE THE WEIGHT OF THE MACHINE OVER A WIDER AREA OF THE RAMP INCREASING ITS ABILITY TO HANDLE MORE LOAD. NARROW WHEELBASES PUT MORE WEIGHT ON A SMALLER AREA OF THE RAMP, LOWERING ITS CAPACITY.

1. CHECK THE MACHINE'S WHEELBASE.



2. ONCE YOU KNOW THE WHEELBASE AND RAMP LENGTH, USE THE TABLE BELOW TO WORK OUT WHICH RAMP IS SUITABLE.



Ramp Capacity By Machine Wheelbase		
Code	Capacity @ Wheelbase	Length
LR152530	1.5t @ 1m	2480mm
LR233030	2.0t @ 1m	3000mm
LR303030	3.0t @ 1.2m	3000mm
LR303535	3.0t @ 1.2m	3500mm
LR353535	3.5t @ 1.5m	3500mm
LR403545	4.0t @ 1.5m	3500mm
LR473545	4.7t @ 1.5m	3500mm
LR473550	4.7t @ 1.5m	3500mm
LR593545	5.9t @ 1.5m	3500mm
LRU593550	6.2t @ 2.0m	3500mm
LRU663550	7.0t @ 2.0m	3500mm
LRU823550	9.0t @ 2.0m	3500mm

Specifications					
Code	Description	Beam	Int Width	Ext Width	Weight
LR152530	Standard	64mm	255mm	300mm	14kg
LR233030	Standard	100mm	300mm	360mm	23kg
LR303030	Standard	115mm	300mm	360mm	26kg
LR303535	Standard	115mm	350mm	410mm	36kg
LR353535	Standard	125mm	350mm	410mm	37kg
LR403545	Standard	140mm	450mm	510mm	46kg
LR473545	Standard	155mm	450mm	510mm	48kg
LR473550	Standard	155mm	500mm	560mm	51kg
LR593545	Standard	165mm	450mm	510mm	50kg
LRU593550	Universal	165mm	500mm	560mm	65kg
LRU663550	Universal	170mm	500mm	560mm	67kg
LRU823550	Universal	180mm	500mm	560mm	77kg

Contact your local professional dealer or contact Digga direct

THE BEST DOWNUNDER



QLD, NT

4 Octal Street
Yatala QLD 4207

Ph: (07) 3807 3330

DIGGA NSW, ACT

Unit 2, 36 Bluett Drive
Smeaton Grange NSW 2567
Ph: (02) 4647 1400

DIGGA VIC, SA, TAS

21 - 25 Villas Road
Dandenong VIC 3175
Ph: (03) 9706 6171

DIGGA WA

6/15 Yampi Way
Willeton WA 6155
Ph: (08) 9457 1544

Email: info@digga.com Web: www.digga.com

