

Date:	<i>l</i> ,	1

## **Door Prospect Form**

New Construction	onRemodeling				
Ship Out	Pick Up	Bill to:	_Client	Builder	
Client:					
				· · · · · · · · · · · · · · · · · · ·	
City	State:		_ Zip:		
	Business:		_ Fax:		
			_ Mobile		
Address of Installation	n:				
City _	State:		_ Zip:		
Directions or Shipping	g Instructions:				
Builder:	Supervisor:				
Address:					
City	State:		Zip:		
Phones: Home:	Business:		Fax:		
E-mail:			Mobile		
Architect / Designer: _					
	ome:Business:		Fax:		
E-mail:			Mobile		
Door Specs					
Unit Set up: Single do	oorDouble DoorTransomSideli	ghts			
Style Name or model:	:				
Total dimension of the Unit:width xheight OR Rough Opening:width xheight					
Arch type: FullEyerbowGothic None Radius or Springline					
Finish:					
Foot Boards: YesNoIF YES specify height of footboard					
	OUT when looking at the door from the outside				
Which door should be active on a set of double doors? RightLeft when looking at the door from the outside.					
Hardware location on a single door? RightLeftwhen looking at the door from the outside.					
FROM THE BUILDER	R				
	ud size in a new construction" Total Wall	l width on a remo	ndel "		
Finish of the wall on t	he outside: brick stone stuc	co oth	er		
Glass type: Patterned or clear Thickness: single pane or insulated					
Clade type. I atterned	7 01 01001 111101(10000 0111g10	pario di induiate			
Hardwara Branaratio	on Snoo:				
Hardware Preparation		or			
Standard: 2 1/8" boring, 2 3/8" backset, 5 ½" Center to Center  Std Single Bore with decorative pull handles from Solara and roller latches. Pull handle model #					
Mortise Lock, see our standard mortise lock preparation specs enclosed.					
Floor Level:					
Standard 1 7/8" or commercial 7/8" (Jam & Door level difference)  Type of flooring used: Wood Floors: " wood floor height Marble or stone " marble height					
Type of flooring used. Wood Ploors wood floor fleight - Marble of Storie flarble fleight					
Notoci					
Notes					