



ENDURA TRI-PROOF DUAL WATTAGE CCT LED BATTEN



MICROWAVE
SENSOR

22372 08

220-
240V
AC

20W/
40W

4000lm
MAX

IK08

IP66



TRI-COLOUR
CCT

120°
BEAM
SPREAD

>80
CRI (Ra)

3YR
WARRANTY


The Endura Tri-Proof Dual Wattage CCT LED Batten is a one box solution for multi-purpose commercial or industrial utility applications.

Supplied with Vandal-proof screws and IK08 impact rated.

- Designed to provide high levels of illumination under adverse conditions
- Robust construction to maintain maximum light output and lamp life
- Large terminal blocks and cable entry
- Stainless Steel locking clips for water tight seal
- Easy selectable colour changing temperature (CCT) with an inbuilt switch 3000°K, 4200°K & 5700°K
- Designed for quick and easy installation and maintenance
- Excellent for commercial and residential applications, schools, car parks, security purposes, public buildings, carports and garages
- Dual-Power Selectable: 20W / 40W (Through DIP switch)
- Max Lumen at 40W: 4000lm(4200°K)
- This Tri-Proof batten has impact, corrosion and weather resistant body
 - IP66 Weatherproof Rating
 - IK08 Impact Rating
- Vandal-proof screws included
- 220-240V AC 50Hz
- 3 year warranty

APPLICATIONS

- Office and school lighting: office room, meeting room, class room.
- Commercial lighting: shopping mall, super market, retailer shops.
- Workshop and garage.



**Terminal block:
PA14, 500V, VDE**



ENDURA TRI-PROOF DUAL WATTAGE CCT LED BATTEN

TECHNICAL SPECIFICATIONS

Operating voltage:	220-240V / 50Hz
Class:	Class I (1)
Wattage:	20W / 40W Switchable
Lumens:	4000 Lumen max
Colour temperature:	3000°K (Warm white) 4200°K (Cool White) 5700°K (Daylight)
Power/Lumens/CCT:	20W 2100lm 3000°K 20W 2200lm 4200°K 20W 2200lm 5700°K 40W 3600lm 3000°K 40W 4000lm 4200°K 40W 4000lm 5700°K
Beam Angle:	120 degrees
Colour rendering index:	≥ 80
Power factor:	≥ 0.9
Dimmable:	No
Rated lifetime:	30,000hrs @40°C Ambient
Construction:	Polycarbonate (frame & diffuser)
Ingress protection:	IP66
Operating temperature:	TA: 25 degrees Celsius
Warranty:	3 year replacement
Standards:	AS/NZS 60598.1 AS/NZS 60598.2.2 CISPR15

INSTALLATION

Must be installed by a Licensed Electrician

DIP Switch settings:



Detection Area

ON	1	2	
ON	ON	100%	
OFF	ON	75%	
ON	OFF	50%	
OFF	OFF	25%	


Hold Time

ON	3	4	5	
ON	ON	ON	5s	
OFF	ON	ON	30s	
ON	OFF	ON	90s	
OFF	OFF	ON	5min	
ON	ON	OFF	20min	
OFF	OFF	OFF	30min	

Daylight Function

ON	6	7	8	
ON	ON	ON	2lux	
ON	ON	OFF	10lux	
OFF	ON	OFF	30lux	
ON	OFF	OFF	50lux	
OFF	OFF	OFF	Disable	


Ceiling mounting:




Ceiling mounted height: 3m
Sensitivity: 100%/75%/50%/25%
Slow moving speed (Speed: 0.3m/s)
Max. mounting height: 6m*

*At 6m mounting height: 25% / 50% sensitivity is not able to detect motion signal.

Wall mounting:



Wall mounted height: 2m
Sensitivity: 100%/75%/50%/25%
Slow moving speed (Speed: 0.3m/s)



1236mm

	MODEL	COLOUR	DESCRIPTION	BOX SIZE	GROSS WEIGHT	BOX QTY	BARCODE/TUN
RETAIL BOX	22371/08	Grey	Endura Tri-Proof CCT LED Batten	W1243 x H123 x D79 mm	2.2 kg	1 pc	9 312641 223719 >
OUTER CTN	22371/08	Grey	Endura Tri-Proof CCT LED Batten	W1260 x H333 x D263 mm	17.6 kg	8 pc	19312641223716
RETAIL BOX	22372/08	Grey	Endura Microwave Sensor Tri-Proof CCT LED Batten	W1243 x H123 x D79 mm	2.25 kg	1 pc	9 312641 223726 >
OUTER CTN	22372/08	Grey	Endura Microwave Sensor Tri-Proof CCT LED Batten	W1260 x H333 x D263 mm	18.0 kg	8 pc	19312641223723