





COMET

LED **DIMMABLE** LOW GLARE **TRI-CCT** DOWNLIGHTS

- Input voltage: 220-240V AC
- Inbuilt constant current LED driver included
- Housing & heatsink: plastic & aluminium
- Diffuser: PC
- Tri-CCT (3000K/ 4000K/ 6000K) in one fitting
- Rear switch
- CRI: ≥80
- Power factor: 0.9
- Flex & plug: 1m
- Ambient temperature: -20 to 40°C
- Suitable for dimming
- Suitable for 2-way switching
- COMET05-06: IP20 (IP54 for front face only)
- COMET07-08: IP20



COMET05-06 COMET07-08



COMET05



COMET06

Tested & Recommended Dimmers:

BRAND	PART NO.
CLA	VELA
Clipsal	32E450UDM, 31E2PUDM
Clipsal	32ELEDM-WE, 32E450TM
HPM	CAT250T, CAT400T
DIGINET	MEDM

*Please check with Licenced electrician for Min and Max dimmer load

*May be used with other untested dimmers



COMET07
(GIMBAL)



COMET08
(GIMBAL)

PART NO.	DESCRIPTION	LUMENS			WATT	DIMENSIONS	CUTOUT	BOX WEIGHT	BOX SIZE	CARTON QTY
		3000K	4000K	6000K						
COMET05	D/L LED FIXED DIMM BLK RND Low Glare COB TRI	700LM	800LM	750LM	9W	Ø100x85mm	Ø85-90mm	0.3kg	11x11x10cm	1/45
COMET06	D/L LED FIXED DIMM WH RND Low Glare COB TRI	700LM	800LM	750LM	9W	Ø100x85mm	Ø85-90mm	0.3kg	11x11x10cm	1/45
COMET07	D/L LED GIMBAL DIMM BLK RND Low Glare COB TRI	700LM	800LM	750LM	9W	Ø100x85mm	Ø90mm	0.3kg	11x11x10cm	1/45
COMET08	D/L LED GIMBAL DIMM WH RND Low Glare COB TRI	700LM	800LM	750LM	9W	Ø100x85mm	Ø90mm	0.3kg	11x11x10cm	1/45

*Must be installed by a licenced electrician (Installation instructions sheet provided in each product box)