




Contact | Support  
[eglo.com/en/eglo-worldwide](https://eglo.com/en/eglo-worldwide)



## General Information

|                 |               |
|-----------------|---------------|
| Material number | 204794        |
| EAN/UPC         | 9008606215782 |

## Dimensions

|  |      |
|--|------|
| Article Diameter (in mm/in)                    | 1168 |
| Article Height (in mm/in)                      | 295  |
| Height - ceiling to bottom of blade (in mm/in) | 285  |
| Canopy Diameter (in mm/in)                     | 170  |

## Fan

|                       |                   |
|-----------------------|-------------------|
| Motor Type            | DC                |
| Motor Wattage         | 22                |
| Operation Voltage     | 220-240V, 50Hz    |
| Enclosure Colour      | matte white       |
| Enclosure Material    | ABS, UV Resistant |
| Blade Colour (1)      | white matt        |
| Blade Material        | ABS, UV Resistant |
| Blade Quantity        | 3                 |
| Blade pitch in degree | 16°               |
| Adjustable Canopy     | 8                 |
| Downrods optional     | 203376, 203375    |

| Performance                 | 1 (low) | 2    | 3    | 4    | 5     | 6     |
|-----------------------------|---------|------|------|------|-------|-------|
| Wattage by air movement (1) | 2.4     | 3.4  | 4.5  | 7    | 10.9  | 20    |
| RPM (1)                     | 62      | 89   | 110  | 140  | 167   | 200   |
| Air Movement m3/Hr (1)      | 3230    | 5780 | 7390 | 9530 | 11420 | 14620 |

## Controls

|                      |                                |
|----------------------|--------------------------------|
| optional controllers | No                             |
| Battery Quantity     | 2                              |
| Battery Type         | AAA; Alkali; LR03; 1,5V; Micro |


## Features

|          |   |
|----------|---|
| Function | remote control incl.<br>control via remote control<br>timer<br>reversible<br>Night Mode<br>6 speeds |
|----------|---|

# 204795 NOOSA



Contact | Support  
[eglo.com/en/eglo-worldwide](https://eglo.com/en/eglo-worldwide)



## General Information

|                 |               |
|-----------------|---------------|
| Material number | 204795        |
| EAN/UPC         | 9008606215799 |

## Dimensions

|  |      |
|--|------|
| Article Diameter (in mm/in)                    | 1168 |
| Article Height (in mm/in)                      | 295  |
| Height - ceiling to bottom of blade (in mm/in) | 285  |
| Canopy Diameter (in mm/in)                     | 170  |

## Fan

|                       |                   |
|-----------------------|-------------------|
| Motor Type            | DC                |
| Motor Wattage         | 22                |
| Operation Voltage     | 220-240V, 50Hz    |
| Enclosure Colour      | matte black       |
| Enclosure Material    | ABS, UV Resistant |
| Blade Colour (1)      | black matt        |
| Blade Material        | ABS, UV Resistant |
| Blade Quantity        | 3                 |
| Blade pitch in degree | 16°               |
| Adjustable Canopy     | 8                 |
| Downrods optional     | 202979, 202977    |

| Performance                 | 1 (low) | 2    | 3    | 4    | 5     | 6     |
|-----------------------------|---------|------|------|------|-------|-------|
| Wattage by air movement (1) | 2.4     | 3.4  | 4.5  | 7    | 10.9  | 20    |
| RPM (1)                     | 62      | 89   | 110  | 140  | 167   | 200   |
| Air Movement m3/Hr (1)      | 3230    | 5780 | 7390 | 9530 | 11420 | 14620 |

### Controls

|                      |                                |
|----------------------|--------------------------------|
| optional controllers | No                             |
| Battery Quantity     | 2                              |
| Battery Type         | AAA; Alkali; LR03; 1,5V; Micro |



### Features

|          |   |
|----------|---|
| Function | remote control incl.<br>control via remote control<br>timer<br>reversible<br>Night Mode<br>6 speeds |
|----------|---|

# 204796 NOOSA



Contact | Support  
[eglo.com/en/eglo-worldwide](http://eglo.com/en/eglo-worldwide)



## General Information

|                 |               |
|-----------------|---------------|
| Material number | 204796        |
| EAN/UPC         | 9008606215805 |

## Dimensions

|  |      |
|--|------|
| Article Diameter (in mm/in)                    | 1168 |
| Article Height (in mm/in)                      | 295  |
| Height - ceiling to bottom of blade (in mm/in) | 285  |
| Canopy Diameter (in mm/in)                     | 170  |

## Fan

|                       |                   |
|-----------------------|-------------------|
| Motor Type            | DC                |
| Motor Wattage         | 22                |
| Operation Voltage     | 220-240V, 50Hz    |
| Enclosure Colour      | titanium          |
| Enclosure Material    | ABS, UV Resistant |
| Blade Colour (1)      | titanium          |
| Blade Material        | ABS, UV Resistant |
| Blade Quantity        | 3                 |
| Blade pitch in degree | 16°               |
| Adjustable Canopy     | 8                 |
| Downrods optional     | 204751, 204752    |

| Performance                 | 1 (low) | 2    | 3    | 4    | 5     | 6     |
|-----------------------------|---------|------|------|------|-------|-------|
| Wattage by air movement (1) | 2.4     | 3.4  | 4.5  | 7    | 10.9  | 20    |
| RPM (1)                     | 62      | 89   | 110  | 140  | 167   | 200   |
| Air Movement m3/Hr (1)      | 3230    | 5780 | 7390 | 9530 | 11420 | 14620 |

### Controls

|                      |                                |
|----------------------|--------------------------------|
| optional controllers | No                             |
| Battery Quantity     | 2                              |
| Battery Type         | AAA; Alkali; LR03; 1,5V; Micro |

### Features

|          |   |
|----------|---|
| Function | remote control incl.<br>control via remote control<br>timer<br>reversible<br>Night Mode<br>6 speeds |
|----------|---|