



ACCESSORIES

Duct with Carry Bag.

EFI75XX

ELECTRIC DRIVEN PORTABLE VENTILATOR FOR HAZARDOUS LOCATIONS



The EFI75XX (12"/300mm) is intended for use in potentially explosive atmospheres. It features a totally enclosed motor and is IP55 rated. It includes an ABS chemical resistant housing and integral thermal overload protection.

- Built with durable flame retardant and chemical resistant ABS casing.
- Includes two integrated duct adapters and a handy 7.6m extended reach power cord as standard.
- Starter is secured in the flameproof motor enclosure to prevent risk of ignition while powered.
- Comes with integral thermal overload protection to prevent damage from overheating.
- Certificate number: IECEx UL 13.0062X.

IECEx AND ATEX CERTIFICATION

The electrical equipment is certified for use in Group IIB, Zone 1, T6 hazardous atmospheres.

MODEL ORDER CODE	EFI75XX EB7201XX-230
FREE AIR	4,250m³/hr
MOTOR	0.75hp (0.56 kW)
UNIT RATING	IP55
POWER SUPPLY	230V/50Hz
AMPS	3A
WEIGHT	20kg
EQUIPMENT PROTECTION LEVEL	Ex d (motor) Ex de (Junction Box and glands)

