





### Product Description:

- LED Downlight
- Aluminum black finish
- Dali Dimmable
- 45° Beam angle
- 76mm Cut out
- TRI Colour
- Built in 12w LED





### Technical Data:

<b>PRODUCT CODE:</b>	<b>HCP-8521204</b>		
Dimension: unit = mm	Light Fitting = 84mm x 95mm		
Voltage	240v (supplied with LED driver)		
Power	12w		
LED Type	COB LED Chip		
Lumen (±10%)	3000K = 1080lm	4000K = 1120lm	5500K = 1160lm
Colour Temperature (CCT)	3000K + 4000k + 5500k by switch on back of fitting		
Cut out	76mm		
Beam Angle	45°		
Color Rendering Index (CRI)	Ra >90		
Power Supply Efficiency	>95%		
LED Luminous Efficiency	Up to 96lm/W		
Power Factor (PF)	>0.95		
IP Rating	IP44		
Certificate	C-TICK, SAA, CE, CB		
Material	Aluminium + PC		



### Product Description:

- LED Downlight
- Aluminum white finish
- Dali Dimmable
- 45° Beam angle
- 76mm Cut out
- TRI Colour
- Built in 12w LED



### Technical Data:

<b>PRODUCT CODE:</b>	<b>HCP-8531204</b>		
Dimension: unit = mm	Light Fitting = 84mm x 95mm		
Voltage	240v (supplied with LED driver)		
Power	12w		
LED Type	COB LED Chip		
Lumen (±10%)	3000K = 1080lm	4000K = 1120lm	5500K = 1160lm
Colour Temperature (CCT)	3000K + 4000k + 5500k by switch on back of fitting		
Cut out	76mm		
Beam Angle	45°		
Color Rendering Index (CRI)	Ra >90		
Power Supply Efficiency	>95%		
LED Luminous Efficiency	Up to 96lm/W		
Power Factor (PF)	>0. 95		
IP Rating	IP44		
Certificate	C-TICK, SAA, CE, CB		
Material	Aluminium + PC		