

## Product Specifications:

**Material:** Thermoplastic shell- Polycarbonate

**Sealant:** Pre-filled non hardening silicone gel

**IP Rating:** IP67

**Warranty:** 2 years replacement




## Product Benefits:

- Waterproof and corrosion proof-IP67.
- Eliminates need for heat shrink, tape, or sealants.
- Operation temperature for silica inside is  $-40^{\circ}$  to  $120^{\circ}$
- Can be used with 12v DC or 24v DC
- Flame retardant PC shell
- Fixed end cap secures sealant and protects connections
- Swept-wing and hex top help easily tighten and remove.

## Installation Steps:

- Turn off power before installing or removing the connector
- Firmly grasp wires and ensure conductor ends are even.
- Conductors may be twisted or untwisted.
- Turn connector on in one direction until secure
- To remove, turn connector in opposite direction.



IMAGE	PART NUMBER	SUITABLE WIRES	BOX QUANTITY
	<b>HV9911</b>	22-10AWG / 0.3247-5.26 mm <sup>2</sup>	100PCS
	<b>HV9912</b>	22-8AWG / 0.3247-8.37 mm <sup>2</sup>	100PCS
	<b>HV9913</b>	22-6AWG / 0.3247-13.3 mm <sup>2</sup>	100PCS