

General info

Indoor - Ceiling lamps


Ean	8021696290775
Item	AURA PL ROUND 3000K NERO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	0.45 kg
Volume	0.001829 m ³

Technical info

Net weight	0.35 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included NO, electronic
Recessed specifications	65...205 - h. ≥ 26

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	20 W
Emission	Direct
Max consupcion	max 20,00 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°C)	30000 h
CRI	> 80
Light beam	115°
Light beam flux	2050 lm
Useful light flux	1620 lm
Photobiological risk	EXEMPT



General info

Indoor - Ceiling lamps


Ean	8021696306360
Item	AURA PL ROUND 4000K NERO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	0.45 kg
Volume	0.001829 m ³

Technical info

Net weight	0.35 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included NO, electronic
Recessed specifications	65...205 - h. ≥ 26

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	20 W
Emission	Direct
Max consupcion	max 20,00 W
Features LED	LED SMD
CCT LED	4000 K
Duration LED (t. 25°C)	30000 h
CRI	> 80
Light beam	115°
Light beam flux	2100 lm
Useful light flux	1660 lm
Photobiological risk	EXEMPT



General info

Indoor - Ceiling lamps


Ean	8021696290799
Item	AURA PL ROUND 3000K BIANCO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	0.45 kg
Volume	0.001829 m ³

Technical info

Net weight	0.35 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included NO, electronic
Recessed specifications	65...205 - h. ≥ 26

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	20 W
Emission	Direct
Max consupcion	max 20,00 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°C)	30000 h
CRI	> 80
Light beam	115°
Light beam flux	2050 lm
Useful light flux	1620 lm
Photobiological risk	EXEMPT



General info

Indoor - Ceiling lamps

Ean	8021696306346
Item	AURA PL ROUND 4000K BIANCO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	0.45 kg
Volume	0.001829 m ³

Technical info

Net weight	0.35 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included NO, electronic
Recessed specifications	65...205 - h. ≥ 26

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	20 W
Emission	Direct
Max consupcion	max 20,00 W
Features LED	LED SMD
CCT LED	4000 K
Duration LED (t. 25°C)	30000 h
CRI	> 80
Light beam	115°
Light beam flux	2100 lm
Useful light flux	1660 lm
Photobiological risk	EXEMPT