

General info


Outdoor - Recessed lights



Ean	8021696269009
Item	BIT FI ANTRACITE
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.34 kg
Volume	0.000608 m ³

Technical info

Net weight	0.3 kg
Insulation class	III
Protection index	IP65
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	1, On-Off / Phase cut
Power output	5.4-6.4 V DC
Power supply	Required, remoted, not included
Load resistance	IK06
Accessories not included	Remote on-off driver



Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	2 W
Emission	Direct Asymmetrical
Max consumption	max 2,00 W
Features LED	LED SMD OSRAM
CCT LED	3000 K
Duration LED (t. 25°C)	35000 h
CRI	> 80
SDCM	3
Light beam	100*66°
Light beam flux	340 lm
Useful light flux	135 lm

General info


Outdoor - Recessed lights



Ean	8021696269023
Item	BIT FI BIANCO
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.34 kg
Volume	0.000608 m ³

Technical info

Net weight	0.3 kg
Insulation class	III
Protection index	IP65
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	1, On-Off / Phase cut
Power output	5.4-6.4 V DC
Power supply	Required, remoted, not included
Load resistance	IK06
Accessories not included	Remote on-off driver



Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	2 W
Emission	Direct Asymmetrical
Max consumption	max 2,00 W
Features LED	LED SMD OSRAM
CCT LED	3000 K
Duration LED (t. 25°C)	35000 h
CRI	> 80
SDCM	3
Light beam	100*66°
Light beam flux	340 lm
Useful light flux	135 lm