



## General info

### Indoor - Suspensions

|                     |                         |
|---------------------|-------------------------|
| <b>Ean</b>          | 8021696166247           |
| <b>Item</b>         | CARLTON SP12 CROMO      |
| <b>Installation</b> | Suspensions             |
| <b>Guarantee</b>    | 5 years                 |
| <b>Gross weight</b> | 14.8 kg                 |
| <b>Volume</b>       | 0.161448 m <sup>3</sup> |

## Technical info

|                              |                              |
|------------------------------|------------------------------|
| <b>Net weight</b>            | 12.8 kg                      |
| <b>Insulation class</b>      | II                           |
| <b>Protection index</b>      | IP20                         |
| <b>Compliance</b>            | CE                           |
| <b>Operating temperature</b> | 0° ~ +40 °C                  |
| <b>Full load efficiency</b>  | X                            |
| <b>Dimmer</b>                | Determined by the light bulb |
| <b>Power output</b>          | 220-240 V AC                 |
| <b>Power supply</b>          | Not required                 |

## Source info

|                           |                           |
|---------------------------|---------------------------|
| <b>Integrated source</b>  | Light bulb (not included) |
| <b>Replaceable source</b> | No                        |
| <b>Power</b>              | E14 max 12 x 40 W         |
| <b>Emission</b>           | Diffuse                   |
| <b>Max consumption</b>    | -                         |



## General info

### Indoor - Suspensions

|                     |                         |
|---------------------|-------------------------|
| <b>Ean</b>          | 8021696213521           |
| <b>Item</b>         | CARLTON SP12 ORO        |
| <b>Installation</b> | Suspensions             |
| <b>Guarantee</b>    | 5 years                 |
| <b>Gross weight</b> | 14.8 kg                 |
| <b>Volume</b>       | 0.161448 m <sup>3</sup> |

## Technical info

|                              |                              |
|------------------------------|------------------------------|
| <b>Net weight</b>            | 12.8 kg                      |
| <b>Insulation class</b>      | II                           |
| <b>Protection index</b>      | IP20                         |
| <b>Compliance</b>            | CE                           |
| <b>Operating temperature</b> | 0° ~ +40 °C                  |
| <b>Full load efficiency</b>  | X                            |
| <b>Dimmer</b>                | Determined by the light bulb |
| <b>Power output</b>          | 220-240 V AC                 |
| <b>Power supply</b>          | Not required                 |

## Source info

|                           |                           |
|---------------------------|---------------------------|
| <b>Integrated source</b>  | Light bulb (not included) |
| <b>Replaceable source</b> | No                        |
| <b>Power</b>              | E14 max 12 x 40 W         |
| <b>Emission</b>           | Diffuse                   |
| <b>Max consumption</b>    | -                         |