

## General info


### Indoor - Ceiling lamps



<b>Ean</b>	8021696299419
<b>Item</b>	DOT PL ROUND BIANCO 3000K
<b>Installation</b>	Ceiling lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.61 kg
<b>Volume</b>	0.000413 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.6 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	1, TRIAC
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Not required



## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	4 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 4,00 W
<b>Features LED</b>	LED DOB
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 90
<b>SDCM</b>	3
<b>Light beam</b>	40°
<b>Light beam flux</b>	320 lm
<b>Useful light flux</b>	190 lm
<b>Photobiological risk</b>	1

## General info


### Indoor - Ceiling lamps



<b>Ean</b>	8021696299402
<b>Item</b>	DOT PL ROUND NERO 3000K
<b>Installation</b>	Ceiling lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.61 kg
<b>Volume</b>	0.000413 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.6 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Dimmer</b>	1, TRIAC
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Not required



## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	4 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 4,00 W
<b>Features LED</b>	LED DOB
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 90
<b>SDCM</b>	3
<b>Light beam</b>	40°
<b>Light beam flux</b>	320 lm
<b>Useful light flux</b>	190 lm
<b>Photobiological risk</b>	1

## General info


### Indoor - Ceiling lamps



<b>Ean</b>	8021696306513
<b>Item</b>	DOT PL ROUND BIANCO 4000K
<b>Installation</b>	Ceiling lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.61 kg
<b>Volume</b>	0.000413 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.6 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	1, TRIAC
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Not required



## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	4 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 4,00 W
<b>Features LED</b>	LED DOB
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 90
<b>SDCM</b>	3
<b>Light beam</b>	40°
<b>Light beam flux</b>	370 lm
<b>Useful light flux</b>	220 lm
<b>Photobiological risk</b>	1

## General info


### Indoor - Ceiling lamps



<b>Ean</b>	8021696306520
<b>Item</b>	DOT PL ROUND NERO 4000K
<b>Installation</b>	Ceiling lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.61 kg
<b>Volume</b>	0.000413 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.6 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP20
<b>Compliance</b>	CE
<b>Operating temperature</b>	0° ~ +40 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	1, TRIAC
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	Not required



## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	4 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 4,00 W
<b>Features LED</b>	LED DOB
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°C)</b>	50000 h
<b>CRI</b>	> 90
<b>SDCM</b>	3
<b>Light beam</b>	40°
<b>Light beam flux</b>	370 lm
<b>Useful light flux</b>	220 lm
<b>Photobiological risk</b>	1