

General info

Indoor - Wall lamps

| | |
|---------------------|-------------------------|
| Ean | 8021696265575 |
| Item | ESSENCE AP D124 BIANCO |
| Installation | Wall lamps |
| Guarantee | 5 years |
| Gross weight | 1.52 kg |
| Volume | 0.016254 m ³ |

Technical info

| | |
|------------------------------|--|
| Net weight | 1.04 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Full load efficiency | X |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic |
| Adjustability | orizz. 0°-358° |

Source info

| | |
|-------------------------------|-----------------------|
| Integrated source | Integrated LED module |
| Replaceable source | No |
| Power | LED 20 W |
| Emission | Indirect |
| Max consumption | max 20,00 W |
| Features LED | LED SMD |
| CCT LED | 3000 K |
| Duration LED (t. 25°c) | 30000 h |
| CRI | > 80 |
| Light beam flux | 2650 lm |
| Useful light flux | 2130 lm |
| Photobiological risk | 1 |

General info

Indoor - Wall lamps

| | |
|---------------------|-------------------------|
| Ean | 8021696285108 |
| Item | ESSENCE AP D124 NERO |
| Installation | Wall lamps |
| Guarantee | 5 years |
| Gross weight | 1.52 kg |
| Volume | 0.016254 m ³ |

Technical info

| | |
|------------------------------|--|
| Net weight | 1.04 kg |
| Insulation class | II |
| Protection index | IP20 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Full load efficiency | X |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic |
| Adjustability | orizz. 0°-358° |

Source info

| | |
|-------------------------------|-----------------------|
| Integrated source | Integrated LED module |
| Replaceable source | No |
| Power | LED 20 W |
| Emission | Indirect |
| Max consumption | max 20,00 W |
| Features LED | LED SMD |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 30000 h |
| CRI | > 80 |
| Light beam flux | 2650 lm |
| Useful light flux | 2130 lm |
| Photobiological risk | 1 |