

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696268354
<b>Item</b>	FEBE-2 AP ANTRACITE 3000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.85 kg
<b>Volume</b>	0.002016 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.76 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP65
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Load resistance</b>	IK06

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	6 W
<b>Emission</b>	Direct Asymmetrical
<b>Max consumption</b>	max 6,00 W
<b>Features LED</b>	LED SMD
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°C)</b>	30000 h
<b>CRI</b>	> 80
<b>Light beam</b>	-
<b>Light beam flux</b>	500 lm
<b>Useful light flux</b>	160 lm
<b>Photobiological risk</b>	EXEMPT

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696268361
<b>Item</b>	FEBE-2 AP BIANCO 3000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.85 kg
<b>Volume</b>	0.002016 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.76 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP65
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Load resistance</b>	IK06

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	6 W
<b>Emission</b>	Direct Asymmetrical
<b>Max consumption</b>	max 6,00 W
<b>Features LED</b>	LED SMD
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°C)</b>	30000 h
<b>CRI</b>	> 80
<b>Light beam</b>	-
<b>Light beam flux</b>	500 lm
<b>Useful light flux</b>	360 lm
<b>Photobiological risk</b>	EXEMPT