

General info

Indoor - Ceiling lamps


Ean	8021696254272
Item	FLY PL D45 3000K BIANCO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	4.38 kg
Volume	0.025 m ³

Technical info

Net weight	3.7 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	26 W
Emission	Direct
Max consumption	max 26,00 W
Features LED	LED SMD SAMSUNG
CCT LED	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	3700 lm
Useful light flux	2970 lm
Photobiological risk	1



General info

Indoor - Ceiling lamps


Ean	8021696270296
Item	FLY PL D45 4000K BIANCO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	4.4 kg
Volume	0.025 m ³

Technical info

Net weight	3.7 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	26 W
Emission	Direct
Max consumption	max 26,00 W
Features LED	LED SMD SAMSUNG
CCT LED	4000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	3900 lm
Useful light flux	3140 lm
Photobiological risk	1



General info

Indoor - Ceiling lamps


Ean	8021696306599
Item	FLY PL D45 3000K NERO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	4.38 kg
Volume	0.025 m ³

Technical info

Net weight	3.7 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	26 W
Emission	Direct
Max consumption	max 26,00 W
Features LED	LED SMD SAMSUNG
CCT LED	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	3700 lm
Useful light flux	2970 lm
Photobiological risk	1



General info

Indoor - Ceiling lamps

Ean	8021696306605
Item	FLY PL D45 4000K NERO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	4.37 kg
Volume	0.025 m ³

Technical info

Net weight	3.7 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	26 W
Emission	Direct
Max consumption	max 26,00 W
Features LED	LED SMD SAMSUNG
CCT LED	4000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	3900 lm
Useful light flux	3140 lm
Photobiological risk	1