

General info

Indoor - Ceiling lamps


Ean	8021696270326
Item	FLY PL D90 3000K BIANCO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	8.24 kg
Volume	0.09025 m ³

Technical info

Net weight	6.9 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	65 W
Emission	Direct
Max consumption	max 65,00 W
Features LED	LED SMD SAMSUNG
CCT LED	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	9400 lm
Useful light flux	7490 lm
Photobiological risk	1



General info

Indoor - Ceiling lamps


Ean	8021696270241
Item	FLY PL D90 4000K BIANCO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	8.24 kg
Volume	0.09025 m ³

Technical info

Net weight	6.9 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic/osram
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	65 W
Emission	Direct
Max consumption	max 65,00 W
Features LED	LED SMD SAMSUNG
CCT LED	4000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	9900 lm
Useful light flux	7920 lm
Photobiological risk	1



General info

Indoor - Ceiling lamps


Ean	8021696306629
Item	FLY PL D90 3000K NERO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	8.24 kg
Volume	0.09025 m ³

Technical info

Net weight	6.9 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	65 W
Emission	Direct
Max consumption	max 65,00 W
Features LED	LED SMD SAMSUNG
CCT LED	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	9400 lm
Useful light flux	7490 lm
Photobiological risk	1



General info

Indoor - Ceiling lamps

Ean	8021696306636
Item	FLY PL D90 4000K NERO
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	8.24 kg
Volume	0.09025 m ³

Technical info

Net weight	6.9 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic/osram
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	65 W
Emission	Direct
Max consumption	max 65,00 W
Features LED	LED SMD SAMSUNG
CCT LED	4000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	9900 lm
Useful light flux	7920 lm
Photobiological risk	1