

General info

Indoor - Ceiling lamps


| | |
|---------------------|-------------------------|
| Ean | 8021696306643 |
| Item | FLY SLIM PL D35 3000K |
| Installation | Ceiling lamps |
| Guarantee | 5 years |
| Gross weight | 2.93 kg |
| Volume | 0.010507 m ³ |

Technical info

| | |
|---------------------------------|--|
| Net weight | 2.7 kg |
| Insulation class | I |
| Protection index | IP40 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Full load efficiency | X |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic, tridonic |
| Accessories not included | Dimmable driver, upright module |

Source info

| | |
|-------------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 18 W |
| Emission | Direct |
| Max consumption | max 18,00 W |
| Features LED | LED SMD SAMSUNG |
| CCT LED | 3000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 80 |
| SDCM | 3 |
| Light beam | 87° |
| UGR Maximum | < 19 |
| Light beam flux | 2650 lm |
| Useful light flux | 2110 lm |
| Photobiological risk | 1 |



General info

Indoor - Ceiling lamps

| | |
|---------------------|-------------------------|
| Ean | 8021696306650 |
| Item | FLY SLIM PL D35 4000K |
| Installation | Ceiling lamps |
| Guarantee | 5 years |
| Gross weight | 2.93 kg |
| Volume | 0.010507 m ³ |

Technical info

| | |
|---------------------------------|--|
| Net weight | 2.7 kg |
| Insulation class | I |
| Protection index | IP40 |
| Compliance | CE |
| Operating temperature | 0° ~ +40 °C |
| Full load efficiency | X |
| Dimmer | NO, On-Off |
| Power output | 220-240 V AC 50/60 Hz |
| Power supply | In-built, included Replaceable (by qualified operators only), electronic, tridonic |
| Accessories not included | Dimmable driver, upright module |

Source info

| | |
|-------------------------------|---|
| Integrated source | Integrated LED module |
| Replaceable source | Replaceable (by qualified operators only) |
| Power | 18 W |
| Emission | Direct |
| Max consumption | max 18,00 W |
| Features LED | LED SMD SAMSUNG |
| CCT LED | 4000 K |
| Duration LED (t. 25°C) | 50000 h |
| CRI | > 80 |
| SDCM | 3 |
| Light beam | 87° |
| UGR Maximum | < 19 |
| Light beam flux | 2800 lm |
| Useful light flux | 2230 lm |
| Photobiological risk | 1 |