



General info

Indoor - Ceiling lamps



Ean 8021696292236

Item FLY SLIM PL D45 3000K

Installation Ceiling lamps Guarantee 5 years **Gross weight** 4.11 kg Volume 0.016979 m³

Technical info

Net weight 3.75 kg Insulation class Ī **Protection index** IP40 Compliance CE Operating temperature

0° ~ +40 °C

Full load efficiency Χ

Dimmer NO, On-Off


Power output 220-240 V AC 50/60 Hz

Power supply In-built, included

Replaceable (by qualified operators only),

electronic, tridonic

Accessories not included Dimmable driver, uplight module



Source info

Integrated source Integrated LED module

Repleaceable source Replaceable (by qualified operators only)

Power 26 W **Emission** Direct

Max consuption max 26,00 W

Features LED LED SMD SAMSUNG

CCT LED 3000 K Duration LED (t. 25°c) 50000 h CRI > 80 **SDCM** 3 Light beam 87° **UGR Maximum** < 19 Light beam flux 3700 lm **Useful light flux** 2970 lm Photobiological risk 1





General info

Indoor - Ceiling lamps



Ean 8021696306667

Item FLY SLIM PL D45 4000K

Installation Ceiling lamps Guarantee 5 years **Gross weight** 3.88 kg Volume 0.016979 m³

Technical info

Net weight 3.75 kg Insulation class Ī **Protection index** IP40 Compliance CE Operating temperature 0° ~ +40 °C

Full load efficiency Χ

Dimmer NO, On-Off


Power output 220-240 V AC 50/60 Hz

Power supply In-built, included

Replaceable (by qualified operators only),

electronic, tridonic

Accessories not included Dimmable driver, uplight module



Source info

Integrated source Integrated LED module

Repleaceable source Replaceable (by qualified operators only)

Power 26 W **Emission** Direct

Max consuption max 26,00 W

Features LED LED SMD SAMSUNG

CCT LED 4000 K Duration LED (t. 25°c) 50000 h CRI > 80 **SDCM** 3 Light beam 87° **UGR Maximum** < 19 Light beam flux 3900 lm **Useful light flux** 3140 lm Photobiological risk 1