

General info

Indoor - Ceiling lamps


Ean	8021696292250
Item	FLY SLIM PL D60 3000K
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	6.08 kg
Volume	0.069863 m ³

Technical info

Net weight	5.8 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	53 W
Emission	Direct
Max consumption	max 53,00 W
Features LED	LED SMD SAMSUNG
CCT LED	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	7500 lm
Useful light flux	6050 lm
Photobiological risk	1



General info

Indoor - Ceiling lamps

Ean	8021696306674
Item	FLY SLIM PL D60 4000K
Installation	Ceiling lamps
Guarantee	5 years
Gross weight	6.21 kg
Volume	0.069863 m ³

Technical info

Net weight	5.8 kg
Insulation class	I
Protection index	IP40
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic, tridonic
Accessories not included	Dimmable driver, upright module

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	53 W
Emission	Direct
Max consumption	max 53,00 W
Features LED	LED SMD SAMSUNG
CCT LED	4000 K
Duration LED (t. 25°C)	50000 h
CRI	> 80
SDCM	3
Light beam	87°
UGR Maximum	< 19
Light beam flux	8000 lm
Useful light flux	6390 lm
Photobiological risk	1