

General info


Indoor - Wall lamps



Ean	8021696250113
Item	LITE AP NERO
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.5 kg
Volume	0.0008 m ³

Technical info

Net weight	0.34 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz Integrated switch button
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Adjustability	YES



Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	LED 3 W
Emission	Direct
Max consumption	max 3,00 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°C)	20000 h
CRI	> 80
Light beam	23°
Light beam flux	200 lm
Useful light flux	130 lm
Photobiological risk	2
Bulb included	1 - E14 OLIVA 4W 3000K CRI80 SATIN

General info


Indoor - Wall lamps



Ean	8021696250120
Item	LITE AP OTTONE
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.5 kg
Volume	0.0008 m ³

Technical info

Net weight	0.34 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz Integrated switch button
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Adjustability	YES



Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	LED 3 W
Emission	Direct
Max consumption	max 3,00 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°C)	20000 h
CRI	> 80
Light beam	23°
Light beam flux	200 lm
Useful light flux	130 lm
Photobiological risk	2
Bulb included	1 - E14 OLIVA 4W 3000K CRI80 SATIN

General info


Indoor - Wall lamps



Ean	8021696250137
Item	LITE AP NICKEL
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.5 kg
Volume	0.0008 m ³

Technical info

Net weight	0.34 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz Integrated switch button
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Adjustability	YES



Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	LED 3 W
Emission	Direct
Max consumption	max 3,00 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°C)	20000 h
CRI	> 80
Light beam	23°
Light beam flux	200 lm
Useful light flux	130 lm
Photobiological risk	2
Bulb included	1 - E14 OLIVA 4W 3000K CRI80 SATIN

General info


Indoor - Wall lamps



Ean	8021696250106
Item	LITE AP BIANCO
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.5 kg
Volume	0.0008 m ³

Technical info

Net weight	0.34 kg
Insulation class	I
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz Integrated switch button
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Adjustability	YES



Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	LED 3 W
Emission	Direct
Max consumption	max 3,00 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°C)	20000 h
CRI	> 80
Light beam	23°
Light beam flux	200 lm
Useful light flux	130 lm
Photobiological risk	2
Bulb included	1 - E14 OLIVA 4W 3000K CRI80 SATIN