

General info

Technical - Recessed lights


Ean	8021696248189
Item	NOVA FI 12W 3000K BK
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.64 kg
Volume	0.001563 m ³

Technical info

Net weight	0.54 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 90 - h. ≥ 180 , 3-30
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	12 W
Emission	Direct
Max consumption	max 12,00 W
Features LED	LED COB PHILIPS
CCT LED	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 19
Light beam flux	1000 lm
Useful light flux	800 lm



General info

Technical - Recessed lights


Ean	8021696267920
Item	NOVA FI 12W 4000K BK
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.64 kg
Volume	0.001563 m ³

Technical info

Net weight	0.54 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 90 - h. ≥ 180 , 3-30
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	12 W
Emission	Direct
Max consumption	max 12,00 W
Features LED	LED COB PHILIPS
CCT LED	4000 K
Duration LED (t. 25°C)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 19
Light beam flux	1100 lm
Useful light flux	900 lm



General info

Technical - Recessed lights


Ean	8021696248165
Item	NOVA FI 12W 3000K WH
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.64 kg
Volume	0.001563 m ³

Technical info

Net weight	0.54 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 90 - h. ≥ 180 , 3-30
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	12 W
Emission	Direct
Max consumption	max 12,00 W
Features LED	LED COB PHILIPS
CCT LED	3000 K
Duration LED (t. 25°C)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 19
Light beam flux	1000 lm
Useful light flux	800 lm



General info

Technical - Recessed lights


Ean	8021696267937
Item	NOVA FI 12W 4000K WH
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.64 kg
Volume	0.001563 m ³

Technical info

Net weight	0.54 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 90 - h. ≥ 180 , 3-30
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	12 W
Emission	Direct
Max consumption	max 12,00 W
Features LED	LED COB PHILIPS
CCT LED	4000 K
Duration LED (t. 25°C)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 19
Light beam flux	1100 lm
Useful light flux	900 lm



General info

Technical - Recessed lights


Ean	8021696248196
Item	NOVA FI 30W 3000K BK
Installation	Recessed lights
Guarantee	5 years
Gross weight	1.41 kg
Volume	0.003938 m ³

Technical info

Net weight	1.16 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 140 - h. ≥ 200 , 3-50
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	30 W
Emission	Direct
Max consumption	max 30,00 W
Features LED	LED COB PHILIPS
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 22
Light beam flux	3000 lm
Useful light flux	2420 lm



General info

Technical - Recessed lights


Ean	8021696267944
Item	NOVA FI 30W 4000K BK
Installation	Recessed lights
Guarantee	5 years
Gross weight	1.41 kg
Volume	0.003938 m ³

Technical info

Net weight	1.16 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 140 - h. ≥ 200 , 3-50
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	30 W
Emission	Direct
Max consumption	max 30,00 W
Features LED	LED COB PHILIPS
CCT LED	4000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 22
Light beam flux	3250 lm
Useful light flux	2650 lm



General info

Technical - Recessed lights


Ean	8021696248172
Item	NOVA FI 30W 3000K WH
Installation	Recessed lights
Guarantee	5 years
Gross weight	1.41 kg
Volume	0.003938 m ³

Technical info

Net weight	1.16 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 140 - h. ≥ 200 , 3-50
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	30 W
Emission	Direct
Max consumption	max 30,00 W
Features LED	LED COB PHILIPS
CCT LED	3000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 22
Light beam flux	3000 lm
Useful light flux	2420 lm



General info

Technical - Recessed lights

Ean	8021696267951
Item	NOVA FI 30W 4000K WH
Installation	Recessed lights
Guarantee	5 years
Gross weight	1.41 kg
Volume	0.003938 m ³

Technical info

Net weight	1.16 kg
Insulation class	II
Protection index	IP20
Compliance	CE
Operating temperature	0° ~ +40 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	Separate, included Replaceable (by qualified operators only), electronic
Recessed specifications	Ø 140 - h. ≥ 200 , 3-50
Adjustability	vert. 0°-90° , orizz. 0°-360°
Accessories not included	Dimmable driver, Narrow beam lens

Source info

Integrated source	Integrated LED module
Replaceable source	Replaceable (by qualified operators only)
Power	30 W
Emission	Direct
Max consumption	max 30,00 W
Features LED	LED COB PHILIPS
CCT LED	4000 K
Duration LED (t. 25°c)	50000 h
CRI	> 90
Light beam	38°
UGR Maximum	< 22
Light beam flux	3250 lm
Useful light flux	2650 lm