

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696285450
<b>Item</b>	OMEGA AP ROUND ANTRACITE 3000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.55 kg
<b>Volume</b>	0.0012 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.5 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP54
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Adjustability</b>	vert. 0°-90°

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	7 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 7,00 W
<b>Features LED</b>	LED COB
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°c)</b>	25000 h
<b>CRI</b>	> 80
<b>Light beam</b>	120°
<b>Light beam flux</b>	610 lm
<b>Useful light flux</b>	520 lm

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696285474
<b>Item</b>	OMEGA AP ROUND BIANCO 3000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.55 kg
<b>Volume</b>	0.0012 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.5 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP54
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Adjustability</b>	vert. 0°-90°

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Repleaceable source</b>	No
<b>Power</b>	7 W
<b>Emission</b>	Direct
<b>Max consupcion</b>	max 7,00 W
<b>Features LED</b>	LED COB
<b>CCT LED</b>	3000 K
<b>Duration LED (t. 25°c)</b>	25000 h
<b>CRI</b>	> 80
<b>Light beam</b>	120°
<b>Light beam flux</b>	610 lm
<b>Useful light flux</b>	520 lm

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696285467
<b>Item</b>	OMEGA AP ROUND ANTRACITE 4000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.55 kg
<b>Volume</b>	0.0012 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.5 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP54
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Adjustability</b>	vert. 0°-90°

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	7 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 7,00 W
<b>Features LED</b>	LED COB
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°c)</b>	25000 h
<b>CRI</b>	> 80
<b>Light beam</b>	120°
<b>Light beam flux</b>	650 lm
<b>Useful light flux</b>	550 lm

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696285504
<b>Item</b>	OMEGA AP ROUND NERO 4000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.55 kg
<b>Volume</b>	0.0012 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.5 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP54
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Adjustability</b>	vert. 0°-90°

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Repleaceable source</b>	No
<b>Power</b>	7 W
<b>Emission</b>	Direct
<b>Max consupcion</b>	max 7,00 W
<b>Features LED</b>	LED COB
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°c)</b>	25000 h
<b>CRI</b>	> 80
<b>Light beam</b>	120°
<b>Light beam flux</b>	650 lm
<b>Useful light flux</b>	550 lm

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696285498
<b>Item</b>	OMEGA AP ROUND COFFEE 4000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.55 kg
<b>Volume</b>	0.0012 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.5 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP54
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Adjustability</b>	vert. 0°-90°

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Replaceable source</b>	No
<b>Power</b>	7 W
<b>Emission</b>	Direct
<b>Max consumption</b>	max 7,00 W
<b>Features LED</b>	LED COB
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°c)</b>	25000 h
<b>CRI</b>	> 80
<b>Light beam</b>	120°
<b>Light beam flux</b>	650 lm
<b>Useful light flux</b>	550 lm

## General info

## Outdoor - Wall lamps



<b>Ean</b>	8021696285481
<b>Item</b>	OMEGA AP ROUND BIANCO 4000K
<b>Installation</b>	Wall lamps
<b>Guarantee</b>	5 years
<b>Gross weight</b>	0.55 kg
<b>Volume</b>	0.0012 m <sup>3</sup>

## Technical info

<b>Net weight</b>	0.5 kg
<b>Insulation class</b>	I
<b>Protection index</b>	IP54
<b>Compliance</b>	CE
<b>Operating temperature</b>	-15° ~ +45 °C
<b>Full load efficiency</b>	X
<b>Dimmer</b>	NO, On-Off
<b>Power output</b>	220-240 V AC 50/60 Hz
<b>Power supply</b>	In-built, included Replaceable (by qualified operators only), electronic
<b>Adjustability</b>	vert. 0°-90°

## Source info

<b>Integrated source</b>	Integrated LED module
<b>Repleaceable source</b>	No
<b>Power</b>	7 W
<b>Emission</b>	Direct
<b>Max consupcion</b>	max 7,00 W
<b>Features LED</b>	LED COB
<b>CCT LED</b>	4000 K
<b>Duration LED (t. 25°c)</b>	25000 h
<b>CRI</b>	> 80
<b>Light beam</b>	120°
<b>Light beam flux</b>	650 lm
<b>Useful light flux</b>	550 lm