

General info

Outdoor - Wall lamps



Ean	8021696285511
Item	OMEGA AP SQUARE ANTRACITE 4000K
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.65 kg
Volume	0.0012 m ³

Technical info

Net weight	0.6 kg
Insulation class	I
Protection index	IP54
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic
Adjustability	vert. 0°-90°

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	7 W
Emission	Direct
Max consumption	max 7,00 W
Features LED	LED COB
CCT LED	4000 K
Duration LED (t. 25°C)	25000 h
CRI	> 80
Light beam	120°
Light beam flux	650 lm
Useful light flux	550 lm

General info

Outdoor - Wall lamps



Ean	8021696285535
Item	OMEGA AP SQUARE NERO 4000K
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.65 kg
Volume	0.0012 m ³

Technical info

Net weight	0.6 kg
Insulation class	I
Protection index	IP54
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic
Adjustability	vert. 0°-90°

Source info

Integrated source	Integrated LED module
Repleaceable source	No
Power	7 W
Emission	Direct
Max consupcion	max 7,00 W
Features LED	LED COB
CCT LED	4000 K
Duration LED (t. 25°c)	25000 h
CRI	> 80
Light beam	120°
Light beam flux	650 lm
Useful light flux	550 lm

General info

Outdoor - Wall lamps



Ean	8021696285528
Item	OMEGA AP SQUARE BIANCO 4000K
Installation	Wall lamps
Guarantee	5 years
Gross weight	0.65 kg
Volume	0.0012 m ³

Technical info

Net weight	0.6 kg
Insulation class	I
Protection index	IP54
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic
Adjustability	vert. 0°-90°

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	7 W
Emission	Direct
Max consumption	max 7,00 W
Features LED	LED COB
CCT LED	4000 K
Duration LED (t. 25°C)	25000 h
CRI	> 80
Light beam	120°
Light beam flux	650 lm
Useful light flux	550 lm