

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696061467
Item	SNIF AP1 ROUND ANTRACITE
Installation	Wall
Guarantee	5 years
Gross weight	0.89 kg
Volume	0.003211 m ³

Technical info

Net weight	0.75 kg
Insulation class	I
Protection index	IP54
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696144283
Item	SNIF AP1 ROUND BIANCO
Installation	Wall
Guarantee	5 years
Gross weight	0.89 kg
Volume	0.003211 m ³

Technical info

Net weight	0.75 kg
Insulation class	I
Protection index	IP54
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	Determined by the light bulb
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696061474
Item	SNIF AP1 ROUND GRIGIO
Installation	Wall
Guarantee	5 years
Gross weight	0.89 kg
Volume	0.003211 m ³

Technical info

Net weight	0.75 kg
Insulation class	I
Protection index	IP54
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696061450
Item	SNIF AP1 ROUND NERO
Installation	Wall
Guarantee	5 years
Gross weight	0.89 kg
Volume	0.003211 m ³

Technical info

Net weight	0.75 kg
Insulation class	I
Protection index	IP54
Compliance	CE
Operating temperature	-15° ~ +45 °C
Dimmer	Non-dimmable
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-