

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696118666
Item	SNIF AP1 SQUARE GRIGIO
Installation	Wall
Guarantee	5 years
Gross weight	0.67 kg
Volume	0.002723 m ³

Technical info

Net weight	0.6 kg
Insulation class	I
Protection index	IP44
Compliance	CE
Operating temperature	-
Full load efficiency	X
Dimmer	Determined by the light bulb
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696144276
Item	SNIF AP1 SQUARE BIANCO
Installation	Wall
Guarantee	5 years
Gross weight	0.67 kg
Volume	0.002723 m ³

Technical info

Net weight	0.6 kg
Insulation class	I
Protection index	IP44
Compliance	CE
Operating temperature	-
Full load efficiency	X
Dimmer	Determined by the light bulb
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696121963
Item	SNIF AP1 SQUARE ANTRACITE
Installation	Wall
Guarantee	5 years
Gross weight	0.67 kg
Volume	0.002723 m ³

Technical info

Net weight	0.6 kg
Insulation class	I
Protection index	IP44
Compliance	CE
Operating temperature	-
Full load efficiency	X
Dimmer	Determined by the light bulb
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-

General info

Outdoor - Wall lamps


Outdoor wall mounted lamp with direct/indirect light emission



Ean	8021696123080
Item	SNIF AP1 SQUARE NERO
Installation	Wall
Guarantee	5 years
Gross weight	0.67 kg
Volume	0.002723 m ³

Technical info

Net weight	0.6 kg
Insulation class	I
Protection index	IP44
Compliance	CE
Operating temperature	-
Full load efficiency	X
Dimmer	Determined by the light bulb
Power output	220-240 V AC
Power supply	Not required



Source info

Integrated source	Light bulb (not included)
Replaceable source	Replaceable
Power	G9 max 1 x 40 W
Emission	Direct + Indirect
Max consumption	-