


General info

Outdoor - Recessed lights



Ean	8021696255521
Item	WIRE FI D09 ANTRACITE
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.26 kg
Volume	0.000937 m ³

Technical info


Net weight	0.22 kg
Insulation class	I
Protection index	IP65
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	LED 1,5 W
Emission	Direct Asymmetrical
Max consumption	max 1,50 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°c)	20000 h
CRI	> 80
Light beam flux	55 lm
Useful light flux	20 lm
Bulb included	1 - E14 OLIVA 4W 3000K CRI80 SATIN

General info

Outdoor - Recessed lights



Ean	8021696255514
Item	WIRE FI D14 ANTRACITE
Installation	Recessed lights
Guarantee	5 years
Gross weight	0.53 kg
Volume	0.0018 m ³

Technical info

Net weight	0.46 kg
Insulation class	I
Protection index	IP65
Compliance	CE
Operating temperature	-15° ~ +45 °C
Full load efficiency	X
Dimmer	NO, On-Off
Power output	220-240 V AC 50/60 Hz
Power supply	In-built, included Replaceable (by qualified operators only), electronic

Source info

Integrated source	Integrated LED module
Replaceable source	No
Power	LED 4 W
Emission	Direct Asymmetrical
Max consumption	max 4,00 W
Features LED	LED SMD
CCT LED	3000 K
Duration LED (t. 25°C)	20000 h
CRI	> 80
Light beam flux	200 lm
Useful light flux	70 lm
Bulb included	1 - E14 OLIVA 4W 3000K CRI80 SATIN