



Rondo

LED dimmable ceiling light


- 18w LED inbuilt sensor ceiling light
- Input voltage 220-240v ~ 50/60Hz
- Polycarbonate body and diffuser
- Dimmable

Sensor

- Motion detection: 0.5-3m/s
- Detection sensitivity: 10/50/75/100%
- Detection angle: 150° (Wall installation)
- Hold time: 5s/90s/3min/10min
- Corridor function: 0s/30s/10min/Disable
- Daylight sensor: 5/15/50Lux/Disable
- Efficiency: ≥80%
- Mounting height: 6m Max.
- Detection zone Max.: 16m x 16m



Product Code	Alpha Code	Watt	Colour Temp.	Lumens	Dimensions
51050	1R018W4KDS	18w	4000k	1350lm	Ø330 x 100mm




Ceiling Lights



Detection area

Detection area can be reduced by selecting the combination on the DIP switches to fit precisely each application.



Hold time

Refers to the time period the lamp remains at 100% illumination after on motion detected.



Daylight sensor

The sensor can be set to only allow the lamp to illuminate below a defined ambient brightness threshold. When set to Disable mode, the daylight sensor will switch on the lamp when motion is detected regardless of ambient light level. 50lux: twilight operation. 15lux and 5lux: darkness operation only.



Corridor function(Stand-by period)

Refers to the time period the lamp remains at a low light level before it completely switches off in the long absence of people. When set to "+∞", the low light is maintained until motion is detected. When set to "0s", the light will turn off after hold time. NOTE: Daylight sensor is active only when light totally switch off. That means, if set stand-by period on 'Disable' mode, the daylight sensor function will be not available.

