

FLEXI FLH2420

Dimmable 24V low voltage LED Strip IP65

Application

An creative solution for residential and commercial interior spaces

Design Specifications

- High efficiency SMD LED chips with 3M self-adhesive tapes at back
- Roll length 5 m, cuttable every 62.5 mm at scissors symbol ✂
- Connection length can be extended by certain LED drivers, controllers and repeaters
- Dimmable with compatible controller or dimmable constant voltage LED driver; Dimming options -
Type A - trailing edge dimmer
Type B - LED Controller: LT8903DIM , LT8905DIM and LT8904DIM/RP
Type C - 1-10V analogue
- Heat sink and 24V constant voltage LED driver required;
LED CHANNEL OPTIONS SLT1000, SLT3000, SLT3010, SLT3020, SLT3030, SLT3040, SLT3050, SLT4050, SLT5000, Quick connect kit FLC10CS Twin 400 mm fly lead to connect 10 mm strip (pack of 10)
- High colour rendering with high output greater than 1500lm/m



Performance

Dimmer Type - **LED controller**

Technical Specification

Model No.	Description	Input (ac) (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
FLH2420 CW	LED STRIP H.O. 24V IP20 4K 62.5 MM PER CUT	24V DC	20 W/lm	1800 lm/m	4000	80
FLH2420 DL	LED STRIP H.O. 24V IP20 6K 62.5 MM PER CUT	24V DC	20 W/lm	2000 lm/m	6000	80
FLH2420 WW	LED STRIP H.O. 24V IP20 3K 62.5 MM PER CUT	24V DC	20 W/lm	1700 lm/m	3000	80



Model No.	Body Colour
FLH2420 CW	CLEAR
FLH2420 DL	CLEAR
FLH2420 WW	CLEAR

Product Images

