

FLEXI FLL2412/SS10R9

Dimmable 24V low voltage LED Strip IP65

Application

An creative solution for residential and commercial interior and exterior spaces

Design Specifications

- High efficiency SMD LED chips with 3M self-adhesive tapes at back, 12W/m.
- Roll length 20 m, cuttable every 100 mm at scissors symbol ✂
- Connection length can be extended with approved LED drivers, controllers and repeaters
- Dimmable with compatible controller or dimmable constant voltage LED driver; Dimming options -
Type A - trailing edge dimmer
Type B - LED Controller: LT8903DIM , LT8905DIM and LT8904DIM/RP
Type C - 1-10V analogue
- Heat sink and 24V constant voltage LED driver required;
LED CHANNEL OPTIONS SLT1000, SLT3000, SLT3010, SLT3020, SLT3030, SLT3040, SLT3050, SLT4050, SLT5000,
Quick connect kit FLC10CS Twin 400 mm fly lead to connect 10 mm strip (pack of 10)
- SAL heatsink recommended (FLL2406/SS10)



Technical Specification

Model No.	Description	Input (ac) (V)	Power (W)	Lumens (lm)	CCT (K)	CRI
FLL2412WW/SS10R9	LEDSTRIP 24V 12W/m IP65 3K	24V DC	12 W/lm	1000	3000	90
FLL2412CW/SS10R9	LEDSTRIP 24V 12W/m IP65 4K	24V DC	12 W/lm	1000	4000	90
FLL2412DL/SS10R9	LEDSTRIP 24V 12W/m IP65 6K	24V DC	12 W/lm	1000	6000	90

Model No.	Body Colour
FLL2412WW/SS10R9	CLEAR
FLL2412CW/SS10R9	CLEAR
FLL2412DL/SS10R9	CLEAR