





rippleSHIELD dimmer SDD400SFI

 $\label{lem:control} \mbox{Dimmable control with $\it ripple SHIELD$ flicker CONTROL technology, when paired with SAL $\it ripple SHIELD$ downlights$

Application

Ideal for any residential or commercial interior spaces where nuisance ripple induced flicker is visible

Design Specifications

- Digital push button control, with three (3) complimentary key caps provided to suit most switch plates
- Combined with the SAL rippleSHIELD downlights
 Ecogem or Unifit series, the
 rippleSHIELD dimmer eliminates nuisance ripple
 induced flicker between 750-1050Hz once and for all,
 typically found in QLD and NSW regions.In addition, it
 has been found to be enormously successful in
 eliminating LED flicker in off-grid supply environments.
- Smooth dimming performance to 1.0% of light output
- PIXIE connectivity is achieved via the PIXIE / PIXIE PLUS app or paired secondary device
- Refer installation instructions for load compatibility chart.
- Need more info.....slide to the FAQ's below

Performance

- Dimmable YES
- Dimmer Type SFI Trailing edge SDD400SFI ONLY















Technical Specification

Product	Model No.	Input Voltage (V/AC)	Power (W)	Dim (mm)	Body Colour
CONTRACTOR	SDD400SFI	240	250	42(L) × 24(W) × 24(H)	GREY

Patent pending

Due to continued product and technology enhancements, data sourced from sal.net.au shall not form part of any contract and or technical performance guarantee unless expressly confirmed in writing by SAL at the time of order. Products are sold in accordance with SAL Terms and Conditions of sale and all images shown are for illustration purposes only and may vary from the actual colour or finish. Unless specifically stated, all IP ratings nominated for Interior products are from "below the ceiling".





For more information please scan me





