



## DIMENSIONS TECHNICAL DATA FEATURES SPECIFICATIONS

- 70mm Height.
- 252mm Wide
  Cavity depth: 76

Total lumens: 324 Colour temp: 3,000K Power supply: 220-240V

CRI: 80 Wattage: 3.6

Control gear: Included

- Ideal for lighting stairs, pathways and walkways to provide a clear and safe walking environment indoor or out.
- · Can be mounted horizontally or vertically.
- This recessed LED integral bricklight is cast from high grade die cast aluminium with a frosted glass lens.
- Wire direct to mains power supply.
- Driver is integral in the body.
- $\boldsymbol{\cdot}$  Comes pre-wired with 500mmL cable.
- Optional Mounting box available LL8200.

Lamp included: Yes

Air / Moisture Transfer: Closed

IP Rating: IP66

Technology field: LED

Colour: Black





## DIMENSIONS TECHNICAL DATA FEATURES SPECIFICATIONS

- 70mm Height.
- 252mm Wide
  Cavity depth: 76

Total lumens: 324 Colour temp: 3,000K

Power supply: 220-240V

CRI: 80 Wattage: 3.6

Control gear: Included

- Ideal for lighting stairs, pathways and walkways to provide a clear and safe walking environment indoor or out.
- · Can be mounted horizontally or vertically.
- This recessed LED integral bricklight is cast from high grade die cast aluminium with a frosted glass lens.
- Wire direct to mains power supply.
- Driver is integral in the body.
- $\boldsymbol{\cdot}$  Comes pre-wired with 500mmL cable.
- Optional Mounting box available LL8200.

Lamp included: Yes

Air / Moisture Transfer: Closed

IP Rating: IP66

Technology field: LED

Colour: White