MAXIPENDANT XPM

40W and 60W LED pendants consisting of 4 Japanese made LED's in 3000K, 4000K and 5000K. All colour temperatures have a high colour rendering index (CRI) and high COB lumen outputs. Spun aluminium reflector with floating frosted diffuser for uniform light distribution. Large passive heatsink provides effective thermal management ensuring high output and long lifespan. Supplied with remote driver and 2m MAX suspension cable.

Input Voltage	240V	IP Rating	IP20
Lamp Type	LED	Weight	6250g

XPM40		XPM60	
System Power	46.7W	System Power	64.5W
LED Power	43.2W	LED Power	60W

XPM Dimensions



XPM Trim Colours

Aluminium

XPM Accessories

- Custom Powdercoated Reflector

XPM Technical Specifications

XPM40	3000K	4000K	5000K
COB Lumen Output	5340 lm	5560 lm	5640 lm
Lifetime	50,000hrs (L70)		

XPM60	3000K	4000K	5000K
COB Lumen Output	6340 lm	6620 lm	6680 lm
Lifetime	50,000hrs (L70)		

Power Factor	> 0.95
Input Voltage	100V - 240V AC 50/60 Hz
Protection	Thermal and Short Circuit
Dimming	DALI* 1-10v* Available on request

XPM Order Code

XPM404 - *800* mm - Dim

Base Fitting
- XPM403 40W 3000K
- XPM404 40W 4000K
- XPM405 40W 5000K*
- XPM603 60W 3000K
- XPM604 60W 4000K
- XPM605 60W 5000K*

Suspension height *(mm)*
- *xx* mm Cable suspension height - max (3m)

Dimming
- DALI Dali Digital Dimming
- 1-10 1-10v Analog Dimming

* Special Order

TREND
LIGHT BY SOLID STATE
Level 3, 290-292 Coward Street, Mascot, NSW, 2020
Ph: (02) 9669 8888 Fax: (02) 9669 8899 Email: sales@trendlighting.com.au