



3X5-F-G Series

VBLFT-325-F-G



Featuring a high quality aluminium body, and an energy saving of up to 60% - the LED Green Tube Lamps make great direct replacements for T8 fluorescent lamps. Suitable for Emergency & Eye wash stations.

Features & Benefits

• Green LED tubes are mainly used in chemical "Eye Wash Stations". This is more based around risk assessment as the colour green is associated with a medical facility. The green light readily identifies where the Eye Wash Stations are located for ease of finding in an emergency.

Specifications

SKU	VBLFT-325-F-G
Luminaire efficacy	70 lm/W
EAN	9340994017495
Light Colour	Green
Wattage	10 W
Lumen output	700 lm
IP rating	20
Beam Angle	120 Degrees
Base Type	G13
Diameter	29 mm
Length	588 mm
Lifespan	50000 Hours
Warranty	3 Years
Dimmable	Non-Dimmable
LED source	Epistar
Material	Aluminium Body with Frosted Green PC Cover
Accessories	Also available in Yellow
Lamp Type	LED
Input voltage	80-265VAC/50Hz
Diffuser	Frosted
Weatherproof	Non-weatherproof
Working temperature	-20°C ~45°C
Box Qty	25



Dimensional Drawings



Photometric information available upon request.







3X5-F-G Series

VBLFT-345-F-G



Featuring a high quality aluminium body, and an energy saving of up to 60% - the LED Green Tube Lamps make great direct replacements for T8 fluorescent lamps. Suitable for Emergency & Eye wash stations.

Features & Benefits

• Green LED tubes are mainly used in chemical "Eye Wash Stations". This is more based around risk assessment as the colour green is associated with a medical facility. The green light readily identifies where the Eye Wash Stations are located for ease of finding in an emergency.

Specifications

SKU	VBLFT-345-F-G
Luminaire efficacy	70 lm/W
EAN	9340994017501
Light Colour	Green
Wattage	18 W
Lumen output	1260 lm
IP rating	20
Beam Angle	120 Degrees
Base Type	G13
Diameter	29 mm
Length	1198 mm
Lifespan	50000 Hours
Warranty	5 Years
Dimmable	Non-Dimmable
LED source	Epistar
Material	Aluminium Body with Frosted Green PC Cover
Accessories	Also available in Red, Blue & Yellow
Lamp Type	LED
Input voltage	80-265VAC/50Hz
Diffuser	Frosted
Weatherproof	Non-weatherproof
Box Qty	25



Dimensional Drawings



Photometric information available upon request.

