

DIGITAL MULTIMETER

Model : V 830 L

3 ½ DIGITS (1999 Counts)

BUILT-IN STAND & HOLSTER

**WITH BACK-LIGHT
& DATA HOLD**

10 MΩ INPUT IMPEDANCE

**200 MΩ RANGE
& SQUARE WAVE OUTPUT**

**MANUAL RANGING WITH
CONTINUITY BUZZER**



LARGE LCD DISPLAY

SPECIFICATIONS		
DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 500 V
	Basic Accuracy	± (0.5 % reading + 2 digits)
	Input impedance	10 M Ω
AC Voltage	Range	200 V, 500 V
	Basic Accuracy	± (1.2 % rdg + 10 digits)
	Freq. Response	40 ~ 400 Hz
DC Current	Range	2 mA, 20 mA, 200 mA, 10 A
	Basic Accuracy	± (1 % rdg + 2 digits)
Resistance	Range	200 Ω, 2 K Ω, 20 K Ω, 200 K Ω, 20 M Ω, 200 M Ω
	Basic Accuracy	± (0.8% rdg + 5 digits)
Square Wave Output	Available	
Other Functions / Facilities	Diode Test, Continuity Test, Back-Light & Data Hold	
Power Source	9 V (6F22)	
Accessories Supplied	Test Leads, User Manual & Battery (Installed / Kept Aside). Holster Optional.	
Dimension & Weight	150 x 73.5 x 35 mm & Approx. 156 gms. (Including Battery)	