

VAR TECH®
Quality • Reliability • Economy

V SERIES

**DIGITAL
MULTIMETER**

Model : V 92 T

**3 1/2 Digits
TRUE RMS**

Manual Ranging

**LARGE Fine L.C.D.
WHITE BACK LIGHT**

**Auto Power Off & Data Hold
2 MHz Auto Ranging Frequency
Meas. Range**

**Auto Ranging Capacitance
Measurement (20 nF ~ 2000 µF)
WITH HOLSTER**



SPECIFICATIONS

DC Voltage	Range	200 mV, 2 V, 20 V, 200 V, 600 V
	Basic Accuracy	± (0.5 % rdg + 3 digits)
AC Voltage	Range	2 V, 200 V, 600 V - TRUE RMS
	Basic Accuracy	± (0.8 % rdg + 5 digits) 40 ~ 1 KHz Freq., Response (Sine & Triangular) / 40 ~ 200 Hz (Others).
DC current	Range	20 mA, 200 mA, 10 A
	Basic Accuracy	± (1.2 % rdg + 8 digits)
AC current	Range	200 mA, 10 A - TRUE RMS
	Basic Accuracy	± (1.5 % rdg + 15 digits). 40 ~ 200 Hz Freq., Response.
Resistance	Range	200 Ω, 20 K Ω, 200 K Ω, 20 M Ω
	Basic Accuracy	± (0.8 % rdg + 5 digits)
Capacitance	Range	20 nF, 200 nF, 2 µF, 20 µF, 200 µF, 2000 µF.
	Accuracy	± (3.5 % rdg + 20 digits)
Frequency	Range	10 Hz, 100 Hz, 1 KHz, 10 KHz, 100 KHz & 2 MHz
	Basic Accuracy	± (1 % rdg + 10 digits)
Continuity Test & Diode Test		Provided
Other Facilities / Features		Data Hold, Auto Power Off, Low Battery Indication, 2 x 'AAA' Battery Operation.
Accessories Supplied		Holster, Test Leads, User Manual, Battery (Installed / Kept Aside).
Dimension & Weight		150 x 73.5 x 35 mm & Approx. 156 gms. (With Batt.)

* All Specifications & appearances are subject to change without prior notice.