

SOLDERING & DE-SOLDERING TOOL - Model: 722



- ❖ ESD Safe by design.
- ❖ POWERFUL BUILT-IN VACUUM PUMP IMPORTED FROM JAPAN.
- ❖ Sensor closed-loop temperature control for heating system; Precise temperature.
- ❖ Long Life Heater which is 36V powered is fully isolated from mains; Safe and reliable.
- ❖ LED digital display; Temperature calibrates digitally.
- ❖ Auto sleeping available and optional.
- ❖ Suction nozzles and heater are specially designed; High efficiency, Long Life.
- ❖ Heat resistant vacuum hose used.
- ❖ Lead free de-soldering can be achieved as long as the lead free de-soldering gun is equipped.
- ❖ Various sizes of Replacement Nozzles Available.
- ❖ Astonishing heating speed ; Only within 20s to reach 300 °C from room temperature.
- ❖ Relative lower temperature will largely prolong the life of soldering tips.
- ❖ Diaphragm Type Pump, 12V, 2A, Vacuum Pressure : 600 mm Hg.

SPECIFICATIONS - Both Soldering/De-Soldering

Heating Power	:	90 W
Temperature Range	:	200 °C ~ 480 °C
Tip to Ground Potential	:	≤ 2 mV
Tip to Ground Resistance	:	≤ 2 Ω
Dimensions	:	105 (L) * 250 (W) * 165 (H) mm
Weight	:	Approx. 5 Kgs.

* * *

** All Specifications & appearances are subject to change without prior notice.*