



# D.C. POWER SUPPLY - LINEAR

## MODELS : 1502 D & 1803 D

HIGH STABILITY  
CV / CC D.C. POWER SUPPLIES  
WITH COARSE & FINE CONTROLS

**LINE REGULATION** :-

CV :  $\leq 0.01\% + 1 \text{ mV}$

CC :  $\leq 0.2\% + 1 \text{ mA}$

**LOAD REGULATION** :-

CV :  $\leq 0.01\% + 3 \text{ mV}$

CC :  $\leq 0.2\% + 3 \text{ mA}$

**RIPPLE & NOISE** :-

CV :  $\leq 0.5 \text{ mV}_{rms}$

CC :  $\leq 3 \text{ mA}_{rms}$

**ENVIRONMENTAL** :-

0 ~ + 40 °C, R.H. < 90%.

**OPERATING VOLTAGE** :-

220 V AC ( $\pm 10\%$ ), 50 Hz ( $\pm 2 \text{ Hz}$ )

**DIMENSION AND WEIGHT** :-

78 (W) x 161 (H) x 280 (D) mm,

2 ~ 4 Kgs.

**DISPLAY** : 2 L.E.D., METERS of 4 Digits,  
One Each For 'V' & 'I'.

**PROTECTION** : Short Circuit & Overload With Current Limiting



NOW WITH 4  
DIGIT L.E.D.  
METERS & FINE  
CONTROLS

| MODEL       | 1502 D   | 1803 D   |
|-------------|----------|----------|
| O/P VOLTAGE | 0 ~ 15 V | 0 ~ 18 V |
| O/P CURRENT | 0 ~ 2 A  | 0 ~ 3 A  |

\*\*\*

\* All Specifications & appearances are subject to change without prior notice.

